

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2565)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A W.Fir 10" dia., bears N.10°W., 14 lks. dist. mkd. ¼ S BT
A W.Fir 10" dia. bears S.17½°E., 27 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - V.R. Tracy and crew - C.S. File 54/12-48A - Dec. 5, 1966

Corner searched for, not found.

BLM Resurvey by Stephen J. Malloy, Cadastral Surveyor, under Group #1219, Surveyed July/Aug. 1984 - (DCSO records Vol. 47 Page(s) 18094)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 23 S R 8 W
¼ S 26
S 35
1984

from which
A Fir 8" dia., bears N.79 3/4°E., 77 lks. dist. mkd. ¼ S26 BT.
A Fir 8" dia., bears S.89°W., 136 lks. dist. mkd. ¼ S35 BT.

Ronald L Rice - For: Rome Creek Timber 1 LLC - Mar 2015 - M169-31

Found - 1984 BLM brass cap with the following accessories:
13" W.Fir bears N.79¾°E., 50.8' - healed face
15 D.Fir bears S.89°W., 89.8' - healed face
New BTs- 10" D.Fir bears S.86°E., 20.1' - blazed, scribed X BT
12" D.Fir bear N.74°W., 41.8'- blazed, scribed ¼ S26 BT
Steel post adjacent to corner