

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 540340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Les Roberts, LS #1039 - For: International Paper Co. - Jan/Feb. 1981 - M 86-66

Set 1½" x 36" Iron pipe and brass cap, from which
16" Hemlock bears N.19°E., 14.6 ft., scribed.
19" Fir bears S.46°E., 43.8 ft., scribed.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2781, surveyed May/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23416-7)

The center ¼ sec. cor. of sec. 23, established by Roberts, in February, 1981; and is accepted as the cor.; monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd.
from which the remains of the bearing trees mkd. by Roberts
A decayed fir stump, 19" dia., bears N.20°E., 14.9 ft., no marks visible.
A decayed tin-capped fir stump, 23" dia., bears S.46°E., 43.3 ft., no marks visible.
and new bearing trees
A fir, 10" dia., bears S.19½°E., 47.9 ft., mkd. C¼ S23 BT.
A fir, 9" dia., bears S.31°W., 14.9 ft., mkd. X BT.
A steel fence post is alongside the cor., which is in the roots of a fir, 22" dia., on the NE. side.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center and has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle irons were driven alongside each corner unless an existing guard post was noted in the corner description.