

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO recs Vol. 6 Pg 2569)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Fir 12" dia, bears N.64°E., 14 lks. dist. mkd. ¼ S BT
A Laurel 8" dia., bears S.72°E., 49 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb/March 1967 - C.S. File 54/12-27

Found - Orig. 12" now 42" Fir, alive, N.56°E., 9.2 ft. (Rec. N.64°E.), shows lower scar, upper scar chopped open 16" deep to burl wood.
Orig. 8" now 13" Laurel S.72°E., 32.3 ft., lower blaze previously opened and shows "BT" scribe. Open upper blaze and find "¼S" scribe and reverse.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
¼ S 14
S 23
1967

New BTs- 12" D.Fir N.41½°E., 25.1 ft. mkd. ¼ S14 CS BT.
11" D.Fir S.26°E., 42.2 ft. mkd. ¼ S23 CS BT.
Corner lies on westerly slope approx. 27.5 ft. E. of small creek.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2781, surveyed May/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23408-9)

The ¼ sec cor of secs 14 & 23, perpetuated by the Douglas Co Surveyor's Office in 1967; monumented with an iron post, 1½" dia firmly set, projecting 10" above ground, with brass cap (properly) mkd from which the remains of the original bearing trees

A decayed fir stump, 38" dia., bears N.58°E., 9.2 ft., with no marks visible on open blaze. (Record, N.64°E.)

A madrone snag, 18" dia., bears S.72°E., 32.3 ft., with illegible scribe marks visible on partially healed blaze at waist height and no marks visible on decayed partially healed blaze at base.

and the remains of the BTs mkd. by the Douglas Co Surveyor's Office

A decayed fir high stump, 11" dia., bears N.40½°E., 25.0 ft., with a healed blaze. Stump leans W.

A fir, 27" dia., bears S.26°E., 42.3 ft with a healed blaze and a new bearing tree

A fir, 9" dia., bears N.32¾°E., 24.9 ft., mkd. ¼ S14 BT.

continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center and has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle irons were driven alongside each corner unless an existing guard post was noted in the corner description.