

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2571-72)

-----  
Set a post 3 ft. long, and 3" sq., 2 ft. in ground for 1/4 sec. corner, mkd. 1/4 S on W. face, from which  
A Fir 10" dia., bears N.85°E., 15 lks. dist. mkd. 1/4 S BT  
A Maple 12" dia., bears S.29°E., 63 lks. dist. mkd. 1/4 S BT

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14434)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

1/4  $\frac{S\ 11}{S\ 14}$   
T 23 S R 8 W  
1967

from which

A Fir 16" dia., bears N.84°W., 93 lks. mkd. 1/4 S11 BT  
A Fir 36" dia., bears S.86°W., 116 lks. mkd. 1/4 S14 BT.

Robert Ward - Dec. 20, 2013 - C.S. 65/82-2 & M167-68 (3/2014)

-----  
Found - 2 1/2" BLM brass cap, 1967  
31" Fir bears N.84°W., 93 lks., healed face.  
49" Fir bears S.86°W., 116 lks., healed face.