

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1554)

Set closing cor. to secs. 35 and 36.
Deposited charred stake and raised mound with trench as per instructions.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13671-72)

Point for the cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 22 S R 8 W

S 35 | S 36

T 23 S R 8 W
S 2
1964

from which

An Oak 19" dia., bears N.17½°E., 89 lks. dist. mkd. T22S R8W S36 BT.

An Oak 15" dia., bears N.64½°W., 107 lks. dist. mkd. T22S R8W S35 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 12, 1992 - C.S. File 64/23-8

Found - 3½" dia. 1964 BLM brass cap on an I.P. flush with ground.

19" now 37" dia. W.Oak with a fully healed single blaze, bears N.17½°E., 58.7 ft. (agrees w/rec.)

15" now a cluster of W.Oaks, brg. distance and fully healed single blaze is on 17" East trunk, East trunk's root crown bears N.64½°W., 70.6 ft. (agrees w/rec.)

New Accessories:

26" dia. W.Oak double blazed and scribed "T22S R8W S36 CS BT" bears N.27°E., 106.4 ft.

5/8" Iron rod with plastic cap 5" below ground bears East 211.2 ft. (T23S R8W NW Cor. S. 1)

Fd. Ok by C. Sweeden, 5/2006 - 2007-0081 A&B

Fd. BC & 3 BTs D. Baker 12/2018 - M175-28 A-C