

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2552)

A point about 250 ft. above a stream. Set a post 4 ft. long, and 4" sq., 2 ft. in the ground for cor. to secs. 35 and 36, marked T23S R8W on N.; S36 on E.; S35 on W., faces with 1 notch on E. and 5 notches on W. edges, from which
A Fir 60" dia., bears N.73½°E., 53 lks. dist. mkd. T23S R8W S36 BT.
A Fir 50" dia., bears N.5½°W., 45 lks. dist. mkd. T23S R8W S35 BT.
A Fir 50" dia., bears S.2°W., 32 lks. dist. mkd. T23S R8W S35 & 36 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Mike Darby & Jim Halterman, crew - March 2, 1964 - C.S. File 49/49-13

Found - 54" D.Fir N.5°W., 29.7 ft., opened and found scribing "3" and "8", appeared to be made with pocket knife, ring count shows right age.
63" D.Fir N.73½°E., 35.0 ft., area on bark shows axe facing, probably had been bark scribed, no scribing visible now.
58" D.Fir S.52°W., (not S.2°W.) 21.1 ft., opened some years ago, fragmentary scribing visible, none legible.
Set brass cap at cor. mkd. County Surveyors Office 1964
T23S R8W S35|S36
New BTs- 10" W.Fir N.20°E., 16.5 ft. mkd. T23S R8W S36 CSBT
9" D.Fir N.75°W., 7.0 ft. mkd. T23S R8W S35 CS BT.

Fd. OK, March 1982 by L. Roberts - M 91-74

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22405-6)

The cor. of secs 35 & 36 on the N. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1964, monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees
A sawed fir stump, 55" dia., bears N.73½°E., 35.0 ft., with no marks visible.
continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 61" dia., bears S.48½°W., 21.1 ft., with no marks visible on an opened blaze. (Record, S.2°W.)
A sawed fir stump, 56" dia., bears N.5½°W., 29.7 ft., with no marks visible on an opened blaze.
and bearing trees mkd. by the Douglas County Surveyors Office
A fir, 22" dia., bears N.21¾°E., 16.3 ft., with a healed double blaze.
A fir, 16" dia., bears N.74°W., 6.8 ft., with a healed double blaze.

DCSO GPS - 8/2021 - added 12/29/2021 - C.S. File 67/51-27
Lat: 43°31'09.54" N Long: 123°36'15.26" W