

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 6 Page(s) 2531)

Set a post cor. secs. 23, 24, 25 and 26, from which
A Fir 15" dia., bears S.25°W., 22 lks. dist.
A Fir 10" dia., bears S.25°E., 37 lks. dist.
A Fir 18" dia., bears N.5°E., 72 lks. dist.
A Fir 10" dia., bears N.10°W., 60 lks. dist.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2566-67)

The Sec. cor., which is a post 4" sq., marked T23S S24 on NE.; R8W S25 on SE.; S26 on SW.; and S23 on NW. faces with 2 notches on S. and 1 notch on E. edges, from which
A Fir 20" dia., bears N.5°E., 72 lks. dist. mkd. T23S R8W S24 BT.
A Fir 14" dia., bears S.25°E., 27 lks. dist. mkd. T23S R8W S25 BT.
The SW. bearing tree being gone, I mark
A Fir 20" dia., bears S.24°W., 38 lks. dist. which I mark T23S R8W S26 BT.
A Fir 14" dia., bears N.10°W., 60 lks. dist. mkd. T23S R8W S23 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Oct. 27, 1960 - C.S. File 52/57 and M 19-75

Found - NW. and SW. BTs now down.
Orig. 18" now 34" Fir N.5°E., 47.5 ft.
Orig. 10" now 15" Fir S.25°E., 24.4 ft. I open and find good scribing "BT".

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
S 23 | S 24
S 26 | S 25
1960

New BTs- 72" R.Fir bears S.71°W., 46.4 ft. scribed S26 T23S R8W CS BT.
24" R.Fir bears N.41½°W., 55.8 ft. scribed S23 T23S R8W CS BT.

Fd. and used in BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group #'s 350 & 538 - surveyed April 1964 - (DCSO records Vol. 32 Page(s) 13538-39)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group #1257, Surveyed May/June 1985 - (DCSO records Vol. 48 Page(s) 18239-40)

The Sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 14" above ground with brass cap mkd. in 1960. from which the remains of the original bearing trees
A Fir stump 44" dia., bears N.5°E., 76 lks. dist. with healed blaze.
A Fir 17" dia., bears S.25°E., 37 lks. dist., with healed blaze.
A root hole bears S.25°W., 22 lks. dist.
A root hole bears N.10°W., 60 lks. dist. with a down Fir alongside, 16" dia., no marks visible.
and remains of BTs mkd. by Byron in 1960
A Fir stump 65" dia., bears S.71°W., 70 lks. dist. with healed blaze.
A Fir stump 22" dia., bears N.41½°W., 85 lks. dist. with scribe marks CS BT visible on opened blaze.
The corner is located in logged area, no suitable trees available.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2781, surveyed May/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23400)

The cor. of secs. 23, 24, 25, & 26, monumented with an iron post, 1½" dia., firmly set, projecting 15" above ground, with a brass cap (properly) mkd. from which the remains of the original bearing trees
A decayed fir stump, 48" dia., bears N.5°E., 50.2 ft., no marks visible.
A fir, 29" dia., bears S.25°E., 24.4 ft., with a healed double blaze.
and the remains of a bearing tree mkd. by Whipple in 1894 and reported by Brooks and Peterson in 1964
A roothole bears S.24°W., 25.1 ft., alongside of which is a down decayed fir, 24" dia., no marks visible. (Record, 14.5 ft.)
and the remains of the bearing trees mkd. by Byron, Deputy Douglas County Surveyor, in 1960 and reported by Brooks and Peterson
A decayed fir stump, 59" dia., bears S.71°W., 46.2 ft., no marks visible.
A decayed fir stump, 21" dia., bears N.41½°W., 56.1 ft., no marks visible.
and new bearing trees
continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A fir, 17" dia., bears N.61°E., 27.3 ft., mkd. T23S R8W S24 BT.
A fir, 16" dia., bears S.63°W., 19.8 ft., mkd. T23S R8W S26 BT.
A fir, 10" dia., bears N.15°W., 37.8 ft., mkd. T23S R8W S23 BT

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center and has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. angle irons were driven alongside each corner unless an existing guard post was noted in the corner description.

Ron Quimby - Crew: R Vincent & J Ogden - 4/2019 - C.S. 65/102-35

Found - DCS0 brass cap (properly mkd)
48" rotted Fir stump N.5°E., 50.2 ft. No visible mks
30" D.Fir S.25°E., 24.4 ft. good scar.
17" D.fir N.61°E., 27.3 ft. good scar.
Down 10" D.Fir N.15°W., 37.8 ft. good scar.
New - 11" D.Fir N.65°W., 19.0 ft. scribed T23 R8 S23 BT
Note - Compass decl. 15½°E.

Scott Toldness - Crew: Jason Raver, D Vaughan & N Peterson -
Dec. 4, 2021 - C.S. File 65/109-43

Found - A 2.5" brass cap, on an iron pipe, 1.1' above the ground, from which:
A Fir, 18" dia., bears N.52½°E., 27.3' dist (rec. N.61°E., 27.3'), with healed blazes and BLM tag by "JH 6/15"
A post bears east, 2.0' dist.
A Fir, 29" dia., bears S.40°E., 24.4' dist. (rec. S.25°E., 24.4'), with tag by "WAITE 4/94"
A Post bears south, 0.3' dist.
A Fir, 19" diam., bears S.55°W., 19.84' dist. (rec. S.63°W., 19.8), with BLM tag
A Fir stump, 65" dia., bears S.71°W., 70 lks. dist.
A Fir snag, 9" dia., bears N.67°W., 19.86' dist. (rec. N.65°W., 19.0), with K-TAG BY "RV 4/19"
New - A Fir, 12" diam., bears N.6½°W., 34.25' dist., scribed "T23SR8WS23BT", with LS washer "90216" below scribe.
Cleared area of debris.
Painted BTs with a 6" band at 6' high.
Added ferrous nails at side center of BTs.
Compass Declination 14½°E