

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2560)

Set a stone 14x12x6 ins., 10" in the ground for cor. to secs. 13, 14, 23 and 24, with 3 notches on S. and 1 notch on E. edges, from which

- A Fir 14" dia., bears N.88°E., 30 lks. dist. mkd. T23S R8W S13 BT.
- A Maple 12" dia., bears S.21°E., 48 lks. dist. mkd. T23S R8W S24 BT.
- A Fir 16" dia., bears S.34°W., 32 lks. dist. mkd. T23S R8W S23 BT.
- A Fir 24" dia., bears N.82°W., 16 lks. dist. mkd. T23S R8W S14 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Oct. 27, 1960 - M 19-75 and C.S. File 52/57

Found four original BTs. All check bearing and distance. NE. BT shows good scribing on previously opened face. Also find stone at corner as recorded.

Set Brass cap at cor. mkd: County Surveyors Office

T 23 S R 8 W
S14|S13
S23|S24
1960

Rescribe now Maple 18", S.21°E., 31.7 ft. "S24 T23S R8W CS BT".

Top of brass cap leans 1.0 ft. to South.

Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 722 - Surveyed Aug 1970/Sept. 1970 - (DCSO records Vol. 35 Page(s) 14486-87)

Fd. OK, Feb. 1981 by L. Roberts - M 86-64

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2781, surveyed May/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23403-4)

The cor. of secs. 13, 14, 23, & 24, perpetuated by Byron, Deputy Douglas Co Surveyor, in 1960; as determined at record bearings & distances from the remains of the original BTs

- A fir, 27" dia., bears N.88°E., 19.8 ft., with a healed blaze.

continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A maple stump with sprouts up to 6" dia. bears S.21°E.,
30.6 ft., no marks visible. (Record, 31.7 ft.)

A fir snag, 30" dia., bears S.34°W., 18.7 ft., with a
healed blaze. (Record and slope, 21.1 ft.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½" dia., 25" in
the ground, in a collar of stone, with brass cap mkd.

T23S R8W
S 14 | S 13
S 23 | S 24
2015

from which

A fir, 15" dia., bears S.48½°E., 32.9, mkd T23S R8W S24 BT

A fir, 9" dia., bears S.28°W., 39.0 , mkd. T23S R8W S23 BT

A fir, 17" dia., bears N.32½°W., 33.3, mkd. T23S R8W S14
BT. A fir, 8" dia., is growing alongside.

The Byron monument, an iron post, 32 ins. long, 1 1/2" dia.,
with brass cap mkd. COUNTY SURVEYORS OFFICE T23S R8W S14 S13
S23 S24 1960, was found lying loose and determined to have
been disturbed from its original position. Remove and
dispose of the iron post.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center and has a magnet
deposited in a white plastic case at the base of the
stainless steel post. Alum. angle irons were driven alongside
each corner unless an existing guard post was noted in the
corner description.