

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2563)

Set a stone 18x14x10 ins., 14" in the ground for ¼ sec.cor. mkd. ¼ S. on N. face, from which
A Laurel 20" dia., bears S.65°E., 9 lks. dist. mkd. ¼ S BT
A Fir 20" dia., bears S.79°W., 65 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Jan/Feb 1967 - C.S. File 54/12-57

Found - Orig. 20" now 30" Laurel S.65°E., 5.9 ft., open on back side and find old reverse axe face. No scribe. Alive.
Orig. 20" now 46" Fir S.79°W., 42.9 ft. Open and find reverse axe notch and part of "B" scribe. BT now hollow and badly decayed.
No trace of stone called for at corner.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
¼ S 14 | S 13
1967

New BTs- 9" D.Fir N.83°W., 10.8 ft. mkd. ¼ S14 CS BT.
6" D.Fir S.25°W., 32.2 ft. mkd. ¼ S14 CS BT.
9" Laurel S.59°E., 36.0 ft. mkd. ¼ S13 CS BT.
Corner lies on steep West slope, 25 ft. North of top of ridge, course generally E. and W.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14429)

The ¼ sec.cor. of sec. 13 only, on the W. bdy. of sec. 13, perpetuated and recorded by Tracy in 1967, monumented with an iron post, 1½" dia., firmly set, projecting 8" above ground with brass cap as mkd. in 1967
from which the original bearing trees
A Madrone 25" dia., bears S.65°E., 9 lks. dist. with fragmentary scribe marks visible on opened blaze.
A Fir 40" dia., bears S.79°W., 65 lks. dist. with no marks visible on opened and rotted blaze.
and bearing trees mkd. by Tracy
A Madrone 8" dia., bears S.59°E., 56 lks. dist. with scribe marks ¼ S13 CS BT visible on open double blaze.
A Fir 8" dia., bears S.25°W., 49 lks. dist. with scribe marks ¼ S14 CS BT visible on open double blaze.

(Cont. Next Page)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 10" dia., bears N.83°W., 16 lks. dist. with scribe marks ¼ S14 CS BT visible on open double blaze.
Add marks BLM 1967 to brass cap.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, crew - April 23, 1973 - C.S. File 56/25-13

Found 1967 DCSO brass cap mkd. T23S R8W ¼ S14|13. Dependent resurvey has changed this to ¼ S13 only. Remark Brass cap for sec. 13 only. Destroy BTs for sec. 14.
New BT - 28" D.Fir N.63°E., 32.0 ft. scribed ¼ S13 CS BT.
BLM brass cap bears South 7.3 ft. mkd. for sec. 14, T23S R8W.

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18284-85)

The ¼ sec. cor. monumented with an iron post 1½" dia., firmly set, projecting 8" above ground with brass cap stamped in 1967 from which the original bearing trees
A Madrone 26" dia., bears S.65°E., 9 lks. dist., with open blaze, no marks visible.
A Fir 45" dia., bears S.79°W., 65 lks. dist. with opened and rotted blaze, no marks visible.
and bearing trees mkd. by Tracy in 1967
A Madrone 11" dia., bears S.59°E., 56 lks. dist., with scribe marks ¼ S13 CS BT visible on partially healed blaze.
A Fir 10" dia., bears S.23½°W., 49 lks. dist., with illegible scribe marks on partially healed blaze. (Rec. S.25°W.)
A Fir 12" dia., bears N.83°W., 16 lks. dist. with partially healed blaze, no marks visible.
and a bearing tree of no record
A Fir 31" dia., bears N.63°W., 48 lks. dist., with healed blaze.