

PRIMARY CORNER DESCRIPTION C C for Secs. 11 & 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2571)

At a point 1.67 chs. South of cor. to secs. 11, 12, 13 and 14, at which point I set a stone 12x10x8 ins., 8" in the ground for a closing corner to secs. 11 and 14, marked C C with 4 notches on S. and 1 notch on E. edges, from which

- A Fir 10" dia., bears N.89°W., 46 lks. dist. mkd. T23S R8W S11 BT.
- A Dogwood 10" dia., bears S.20°W., 116 lks. dist. mkd. T23S R8W S14 BT.
- A Fir 20" dia., bears S.87½°E., 74 lks. dist. mkd. T23S R8W CC S11 and 14 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Jan/Feb. 1967 - C.S. File 54/12-54

Found - Orig. 10" now 42" Fir N.89°W., 30.4 ft., alive, shows good scars. Rescribe "T23S R8W S11 CC CS BT" in bark.

- Orig. 20" now 40" Fir S.87½°E., 48.8 ft. alive, shows good scars. We do not open.
- Orig. 10" now 14" Dogwood S.20°W., 76.6 ft., now 7 ft. high stub, previously opened and shows "S R8W BT" in very poor condition.

No trace of stone called for.

Set Brass cap at cor. mkd: County Surveyors Office

T 23 S	
S 11	CC
S 14	
	1967

New BTs- 5" Maple S.74°W., 26.4 ft. mkd. CC S14 CS BT.
 7" D.Fir S.54°E., 12.6 ft. mkd. CC S11|S14 CS BT.
 This corner lies on very steep, North slope. Sec. cor. for 12 & 13 bears North 110.2 ft.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14430)

The closing corner of secs. 11 and 14, perpetuated and recorded by Tracy in 1967, monumented with an iron post 1½" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1967, from which the original bearing trees:

- A Fir 36" dia., bears N.89°W., 46 lks. dist. with healed blaze. Remarked by Tracy in 1967; scribe marks T23S R8W CC BT visible on bark blaze. (Cont. Next Page)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 600478

PRIMARY CORNER DESCRIPTION C.C. for Secs. 11 & 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 34" dia., bears S.87½°E., 74 lks. dist. with healed blaze.
and bearing trees marked by Tracy
A Maple 5" dia., bears S.74°W., 40½ lks. dist. with scribe marks S14 CC CS BT visible on open double blaze.
A Fir 7" dia., bears S.54°E., 19 lks. dist. with scribe marks CC S11|S14 CS BT visible on open double blaze.
Add marks BLM 1967 to brass cap.