


PRIMARY CORNER DESCRIPTION East 1/4 cor. for Sec. 11 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14431)

-----  
 Point for the 1/4 sec. cor. of sec. 11 only, at midpoint latitudinally, on the E. bdy. of the section.

Set an iron post 28" long, 2 1/2" dia., 25" in the ground with brass cap mkd:



from which

A W.Fir 15" dia., bears N.89°W., 100 lks., mkd. 1/4 S11 BT.

A W.Fir 6" dia., bears S.69°W., 42 lks. mkd. 1/4 S11 BT.

Fd. BC, 1 BT & 1 BT stump by C. Sweeden, 11/2008 - 2009-0015A

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 2/4/2019 - C.S. File 67/49-11

-----  
 Found - A 2 1/2" o.d. iron pipe by Peterson, in 1967, firmly set, projecting 4" above the ground with a 3 1/4" dia. brass cap (properly) marked

Original BTs by Peterson in 1967 -

A 20"x 2' tall very rotted W.fir stump bears S.71°W., 26.5 ft. with a healed blaze. (Rec. S.69°W.)

A 31" dia. W.Fir bears N.89°W., 66.0 ft. with a healed blaze as per record.

New BT- A 12" dia. maple bears N.22 3/4°E., 66.7 ft. scribed "1/4 S11 CS" & "BT" on a double blaze.

A 30" dia. D.Fir bears S.44 1/2°E., 10.9 ft. scribed "1/4 S11" & "CSBT" on a double blaze.

A 15" dia. maple bears N.7°W., 64.4 ft. scribed "1/4 S11" & "CSBT" on a double blaze. Steel fence post approximately 2 ft. South

Note - The corner falls on a North slope in mixed timber approximately 50 ft south of Mehl Creek County Road No. 11.

All BTs have BT Tags attached. All new BTs have double blazed faces with bearing measured to the center of the tree at the root crown and distances measured to a 4" MAGHUB nail in the side and center of the root crown.

GEODETIC COORDINATES (NAD 83)

Latitude: 43°35'04.00" N. Longitude: 123°36'15.51" W.

Compass declination: 14 3/4° E.