

PRIMARY CORNER DESCRIPTION M.C. on West bdy. Sec. 12

Alias 966050 Description M.C. on left bank Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 6 Page(s) 2533)

Intersect left bank of Umpqua River and set meander post, from which

An Oak 24" dia., bears S.29°E., 160 lks. dist.

An Oak 12" dia., bears S.4°W., 255 lks. dist.

Arnold G. Gibson, Asst. Engineer - Oregon State Board of Forestry - April 22, 1957 - C.S. File 42/258 and M 5-19

Found - Orig. 24" Oak bears S.29°E., 160 lks., now 26" stump, burnt log on ground, face not cut out.

12" Oak bears S.4°W., 225 lks., now 18" stump, BT scribe visible, log on ground, 11 scribe visible.

Set a 1½" x 36" galv. iron pipe with a 3" bronze cap mkd. "OREGON STATE BOARD OF FORESTRY MC S11 S12 1957 RS 359", 34" in ground and from which

31" Maple bears S.44°W., 37.0 ft. scribed S11 MC BT RS 359.

18" triple Myrtle bears N.54½°W., 75.6 ft., scribed S11 MC BT.

OSBF metal location poster on 31" Maple BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14432)

(63.97 chains)

Left bank of Umpqua River, course N.75°W; bank is 16 ft. high. Point selected for the witness cor. to the meander cor. of secs. 11 and 12.

Set an iron post 28" long, 2½" dia., 26" in the ground with brass cap mkd.7

MC
\
W↑C
S 11|S 12
T 23 S|R 8 W
1967

from which

A Maple 18" dia., bears S.30°E., 61 lks. dist. mkd. T23S R8W S12 WC MC BT.

A W.Oak 28" dia., bears S.80°W., 157 lks. dist. mkd. T23S R8W S11 WC MC BT.

(64.70 chains)

The original meander cor. of secs. 11 and 12, determined at record bearing and distance from the original bearing trees (Cont. Next Page)

PRIMARY CORNER DESCRIPTION M. C. on West bdy. Sec. 12

Alias 966050 Description M.C. on left bank of Umpqua River
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

A sawed W.Oak stump 34" dia., bears S.29°E., 160 lks. dist. with no marks visible on opened and rotted blaze.
 A sawed W.Oak stump 25" dia., bears S.4°W., 255 lks. dist. with scribe marks BT visible on opened blaze.
 and bearing trees mkd. by Gibson in 1957
 A Maple 35" dia., bears S.44°W., 56 lks. with healed blaze
 A Myrtle 22" dia., bears N.53°W., 120 lks. dist. with scribe marks 11 MC BT visible on open blaze.
 The corner point falls below high water line; no permanent established.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
 Stephen J. Flause - 5/26/2009 - C.S. File 67/28-34

Found - 1957 Bronze cap on a 1½" dia., iron pipe is found 2 ft. below ground. OREGON STATE BOARD OF FORESTRY

M C

 S11 | S12
 1957

1967 3" Brass cap on a 2½" dia., iron pipe protrudes 1" out of ground U.S. DEPT. OF INTERIOR

M C

 W | C
 S11 | S12
 T23S R8W
 BLM

BUR. OF LAND MANAGEMENT

From 1957 OSBF MC
 No OBTs found.
 1957 NW BT gone.
 31" now cluster of 3 large maples with the most Northerly maple having a 45" dia., trunk, no blaze evident. 1957 rec. S.44°W., 37.0 ft. hits northerly trunk (1967 BLM calc. position probably went to center of Maple cluster) 1957 BT
 1967 BLM WC MC BC/IP bears S.1°W., 52.3 ft.

From 1967 BLM WC MC
 18" now down & rotted maple agrees well with record (S.30°E., 40.3 ft.) 1967 BT.
 1967 SW BT gone.
 1957 OSBF BC/IP bears N.1°E., 52.3 ft. (1967 BLM calc. position of orig. MC N.0°08'E., 48.2 ft.)
 Found metal fence post bears N.17°E., 13.2 ft.

New - At 1957 OSBF BC/IP
 Set metal witness post & sign along side BC/IP

continued next page

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 600566

PRIMARY CORNER DESCRIPTION M.C. on West bdy. Sec. 12

Alias 966050 Description M.C. on left bank Umpqua River

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

From 1967 BLM BC/IP

13" dia., maple double blazed & scribed "WC MC S12
CS BT" bears S.28°E., 34.7 ft.

Campbell Purple water spigot on 1" galv. IP sticking
3 ft. out of ground, bears S.44°W., 54.7 ft.

Note - Corners lie on south bank of Umpqua River.
Compass decl. 16¼°E.