

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 600573

PRIMARY CORNER DESCRIPTION M.C. on West bdy. Sec. 12

Alias <u>967040</u>	Description <u>M.C. on right bank of Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 6 Page(s) 2533)

An Ash 6" dia., meander post, from which
An Ash 9" dia., bears N.80°W., 66 lks. dist.
An Oak 18" dia., bears N.5°E., 60 lks. dist.

Survey by Arnold G. Gibson, Asst. Engineer, Oregon State Board of Forestry - April 22, 1957 - M 5-19 and C.S. File 42/258

No evidence of original corner found.
Reestablished corner by setting a 1½" x 36" galv. iron pipe with 3" bronze cap mkd. "OREGON STATE BOARD OF FORESTRY MC S11 S12 1957 RS 359", 34" in ground, and from which a:
32" Maple bears N.29°W., 17.7 ft. scribed S11 MC BT.
38" oak bears N.70°E., 44.6 ft. scribed S12 MC BT RS 359.
OSBF metal location poster on 22" Oak, N.5°E., 45.8 ft.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14432)

Record distance for the meander cor. of secs. 11 and 12, on the right bank of the Umpqua River; there is no remaining evidence of the original corner.