

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 637100

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 1, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 6 Page(s) 2542-43)

Set a post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 15" dia., bears N.16½°W., 61 lks. dist. mkd. ¼ S BT
A Fir 12" dia., bears S.85°W., 80 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Aug. 6, 1965 - C.S. File 49/84-11

Found - 3" square post at corner.
Orig. 15" now 40" Fir, N.16½°W., 40.3 ft., open and shows "¼S" scribe, now snag, 25.0 ft. high.
Orig. 12" now 20" badly rotted stump, S.85°W., 52.8 ft., shows "¼S" scribe.
Set brass cap at cor. mkd: County Surveyors Office 1965
T24S ¼ S 1 R8W
New BTs- 11" D.Fir S.1°E., 15.7 ft. mkd. ¼ S1 CS BT.
8" D.Fir S.67°W., 18.5 ft. mkd. ¼ S1 CS BT.

Fd. OK, March 1982 by L. Roberts - M 91-74

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22404-5)

The ¼ sec. cor. of sec. 1 only, on the N. bdy of the Tp., remonumented by the Douglas County Surveyors Office in 1965, monumented with an iron post, 1¼" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd. from which the remains of an orig. bearing tree
A fir, 40" dia., bears N.11°W., 40.3 ft., with scribe marks ¼ S visible on an open blaze. (Record, N.16½°W.) and bearing trees mkd. by the Douglas County Surveyors Office
A fir, 17" dia., bears S.16½°E., 15.8 ft., with a healed double blaze.
A fir, 12" dia., bears S.58½°W., 13.8 ft., with a healed double blaze.