

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Forrest J. Hales - For: International Paper Co. -
Oct. 23, 1978 - M 74-26

Set 5/8" Iron rod, from which
8" D.Fir bears S.0½°E., 6.0 ft.
12" W.Oak bears N.12½°W., 27.8 ft.
Trees mkd. "BT C ¼ S25 453".

BLM resurvey by Harvey E. Wofford, Cadastral Surveyor, under
Group #1257, Surveyed May/June 1985 - (DCSO records Vol. 48
Page(s) 18242-43)

The center ¼ sec. cor., established and recorded by Hales in
1978, and is accepted as the corner, monumented with an iron
rod, 5/8" dia., firmly set, projecting 4" above ground, from
which bearing trees mkd. by Hales:

A Fir 11" dia., bears S.½°E., 9 lks. dist. with healed
blaze.

A W.Oak 15" dia., bears N.12½°W., 43 lks. dist. with
scribe marks ¼ 453 visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
directly over the iron rod, with brass cap mkd:

T 23 S R 8 W
C ¼ S 25
1985

Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent -
4/2018 - C.S. File 65/101-31

Found - BLM Brass cap (properly mkd)
18" W.Oak N.12½°W., 28.4 ft - good scar.
Rotted Fir stump S.1/2°E., 5.9 ft.
New - 6" D.Fir S.59°W., 17.4 ft. scribed C¼ S25 BT.
Note - Decl. 15½°E

Ron Quimby - Crew: N. Fromdahl & R. Heichel - 4/2019 - C.S.
File 65/102-44

Found - BLM brass cap, properly marked.
18" W.Oak N.12½°W., 28.4 ft - good scar.
6" D.Fir S.59°W., 17.4 ft. vis. scribes.
New - 1/2" I.Rod in 28" fir stump S.40°E., 47.0 ft.
1/2" I.Rod in 16" oak stump N.39°E., 81.0 ft.