TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 6 Page(s) 2532)

Set ¼ sec. post, from which
An Oak 4" dia., bears N.80°W., 5 lks. dist.
A Fir 15" dia., bears S.5°E., 70 lks. dist.

Fd. and used in GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2612)

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group #'s 350 & 538 - surveyed April 1964 -(DCSO records Vol. 32 Page(s) 13539-40)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, to solid rock, with brass cap mkd:

¼ S 24 / S 25
T 23 S R 8 W
1964

from which
A Fir 40" dia., bears N.12°E., 92 lks. dist. mkd. ¼ S24 BT
A Fir 45" dia., bears S.2°W., 64 lks. dist. mkd. ¼ S25 BT

Fd. and used in BLM resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group #1257, Surveyed May/June 1985 - (DCSO records Vol. 48 Page(s) 18241)