

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 6 Page(s) 2532)

-----  
Set ¼ sec. post, from which  
A Fir 6" dia., bears N.30°W., 25 lks. dist.  
A Maple 24" dia., bears S.85°W., 33 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 722 - Surveyed Aug 1970/Sept. 1970 - (DCSO records Vol. 35 Page(s) 14488)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
¼  $\frac{S\ 12}{S\ 13}$   
T 23 S R 8 W  
1970

from which  
A Cedar 10" dia., bears N.70¼°W., 41½ lks. dist. mkd. ¼ S12 BT.  
A Hemlock 12" dia., bears S.23¼°E., 29 lks. dist. mkd. ¼ S13 BT.  
Deposit broken clear glass bottle at base of iron post.

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18281-82)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
From this point, the ¼ sec. cor. of secs. 12 and 13, erroneously positioned by Jelley, bears S.65°40'E., 0.660 chs. dist., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd. and witnessed as described in the official record.  
I remove the iron post, and at the true corner point  
Reset the iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
¼  $\frac{S\ 12}{S\ 13}$   
T 23 S R 8 W  
1986

from which bearing trees mkd. by Jelley  
A Cedar 16" dia., bears N.41¼°E., 33 lks. dist., with scribe marks ¼ S12 BT visible on open blaze.  
A Hemlock 22" dia., bears S.75 3/4°E., 73 lks. dist., with scribe marks ¼ S13 BT.

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. OK, Oct. 1991 by R. Dolan - MLP 1991-0067

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2772, surveyed Sept./Nov. 2014 - (DCSO records Vol. 58 Page(s) 23271)

-----  
The ¼ sec. cor. of secs. 12 & 13, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd.

from which the BTs mkd. by Jelley in 1970, reused by Farmer in 1986

A cedar, 25" dia., bears N.41¼°E., 21.8 ft., with a healed blaze.

A W.Fir, 35" dia., bears S.75¾°E., 48.2 ft., with a healed blaze. (Record, hemlock.)

A steel fence post with a U.S. Forest Service Government Survey Corner sign is alongside the monument.

Fd. BC & 2 BTs by C Sweeden, 8/2016 - M172-39