

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 6 Page(s) 2534)

Set ¼ sec. post, from which
An Oak 15" dia., bears N.24°E., 276 lks. dist.
An Oak 15" dia., bears N.86°W., 755 lks. dist.
No trees convenient S. of line.

Arnold G. Gibson, Asst. Engineer - Oregon State Board of Forestry - April 22, 1957 - C.S. File 42/258 and M 5-19

Found - 15" Oak bears N.24°E., 276 lks., now 24", exposed scribes "¼S".
15" Oak bears N.86°W., 755 lks., now rotted stub in place, old axe work visible.
Set 1½ x 36" galv. iron pipe with 3" bronze cap mkd. "OREGON STATE BOARD OF FORESTRY ¼ S1 S12 1957 RS 359", 28" in ground and from which a
11" Oak bears S.31½°W., 44.0 ft. scribed ¼ S12 BT.
30" Fir bears N.81°E, 203.5 ft. scribed ¼ S1BT RS359
Set - 4"x4"x60" white painted Cedar post 1 ft. NE. of pipe OSBF metal location poster on 30" Oak N.19°W. 2.3 ft

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 6/17/2002 - C.S. File 66/34-10

Found - 1957 OSBF bronze cap/iron pipe. White 4x4 cedar post 1 ft. NE of corner.
Orig. NW BT noted as rotted stump in 1957 now gone.
15" now 30" dia., down Oak fallen on face bears N.24°E., 182.2 ft. (OBT)
30" dia., Oak now 15" dia., Ash with 1957 metal location poster agrees well with record to tag (N.19°W., 2.3 ft.) We now scribe "¼ S1 CS BT" on a single blaze center of tree bears N.19°W., 3.0 ft. (1957)
11" dia., Oak now 17" dia., Ash w/ partially healed single blaze. Scribing visible "¼ S12 BT" bears S.31½°W., 44.6 ft. (rec. 44.0 hits face) 1957
1957 30" now 38" dia., 2 ft. high W.Fir stump we open & find scribe marks "S" bears N.81°E., 204.6 (rec. 203.5 ft. to face.)
New - 17" dia., Ash double blazed & scribed "¼ S12 CS BT" bears S.74°E., 17.7 ft.
16" dia., W.Oak double blazed & scribed "¼ S12 CS BT" bears N.11°E., 174.3 ft.
Compass decl. 17½°E.