

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; and 30, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCS0 records Vol. 6 Page(s) 2460)

Set ¼ sec. post, from which
A W.Oak 10" dia., bears N.70°E., 53 lks. dist.
A W.Oak 14" dia., bears N.35°W., 49 lks. dist.

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCS0 records Vol. 32 Page(s) 13530)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 25 | S 30
R 8 W R 7 W
T 23 S
1964

from which
A Fir 28" dia., bears N.9°E., 23 lks. dist. mkd. ¼ S30 BT
A Fir 23" dia., bears S.69½°W., 106 lks. dist. mkd. ¼ S25 BT.

Fd. OK, March 1983 by D. Bentz - M 90-38 A&B

Fd. and used in BLM resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group #1257, Surveyed May/June 1985 - (DCS0 records Vol. 48 Page(s) 18244)

David Edwards - Crew: Brant Miller & Eric Sprinkle - 4/2023 - C.S. File 65/111-41

Found - 1964 Standard BLM brass capped iron pipe in good condition.

All previous BT's are gone.
New - A 12" Fir scribed "¼ S30 BT" bears S.63°E., 5.2 ft.
A 15" Fir scribed "¼ S25 BT" bears S.44°W., 5.4 ft.
A 5.5 ft. steel post is set 2 ft North.
A 5.5 ft steel post is set 2 ft West.

Note - Compass decl. 15°E.