



TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T23-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy -  
Randall Smith and Stephen Flause, crew - May 30, 1984 - C.S.  
File 62/18-8

-----

Found - BLM 1964 2½" iron pipe with brass cap, properly mkd.  
protruding 6" above ground.

18" now a 28" dia. D.Fir with a single healed blaze,  
bears N.6°E., 268.0 ft. (1964)

37" now a 42" dia. D.Fir with a single healed blaze,  
bears N.39°W.,, 376.9 ft. (1964)

A steel fence post 6 ft. long, set 2 ft. in the  
ground, is alongside East edge of iron pipe.

A 12" rebar 5 ft. long, set 2 ft. in the ground, is  
alongside West edge of iron pipe.

New BTs- 4" dia. D.Fir double blazed and scribed "X BT",  
bears S.46°W., 20.6 ft.

4" dia. D.Fir, double blazed and scribed "X BT",  
bears S.86°E., 81.5 ft.

Corner lies on a gentle North slope. (Map number M 90-38 A  
shows NE. and NW. BTs as not found.)