

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19 of T23-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2459)

-----  
Set post cor. to secs. 18, 19, 13 and 24, from which  
A Fir 15" dia., bears N.45°E., 17 lks. dist.  
A Fir 11" dia., bears S.55°E., 43 lks. dist.  
A Fir 28" dia., bears S.27°W., 30 lks. dist.  
A Fir 4" dia., bears N.10°W., 10 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2560-61)

-----  
The sec.cor. which is a post 4" sq., mkd. T23S S18 on NE.; R7W S19 on SE.; R8W S24 on SW.; and S13 on NW. faces, with 3 notches on N. and S. edges, from which

A Fir 30" dia., bears S.27°W., 30 lks. dist. mkd. T23S R8W S24 BT.

The other bearing trees being gone, I marked new ones as follows:

A Fir 4" dia., bears N.38°E., 73 lks. dist. mkd. T23S R7W S18 BT.

A Maple 18" dia., bears S.29°E., 79 lks. dist. mkd. T23S R7W S19 BT.

A Fir 12" dia., bears N.42°W., 122 lks. dist. mkd. T23S R8W S13 BT.

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 32 Page(s) 13533)

-----  
The Sec. cor., perpetuated with an iron water pipe, 18" long, 2½" dia., firmly set 10" in the ground, from which the remains of an original bearing tree:

A Fir snag 32" dia., bears N.45°E., 17 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 23 S  
R 8 W R 7 W  
S 13 S 18  
S 24 S 19  
1964

from which new bearing trees:

A Fir 10" dia., bears N.34½°E., 27 lks. dist. mkd. T23S R7W S18 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T23-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir 8" dia., bears S.69½°E., 71 lks. dist. mkd. T23S R7W S19 BT.  
A Fir 15" dia., bears S.71 3/4°W., 98 lks. dist. mkd. T23S R8W S24 BT.  
A Fir 25" dia., N.70°W. 96 lks. dist. mkd. T23S R8W S13 BT  
Deposit the water pipe alongside the iron post.  
*(No record found by DCSO of water pipe. Jan. 1997)*

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #987, surveyed July/Nov. 1979 - (DCSO records Vol. 42 Page(s) 16583)

-----

The Sec. Cor., monumented with an iron post 2½" dia., firmly set, projecting 4" above ground, with 1964 brass cap, from which the remains of the original bearing trees;  
A Fir snag 32" dia., bears N.45°E., 17 lks. dist., no marks remaining.  
and trees mkd. by Brooks and Peterson in 1964:  
A Fir 15" dia., bears N.34½°E., 27 lks. dist. with healed blaze.  
A Fir 15" dia., bears S.69½°E., 71 lks. dist. with healed blaze.  
A Fir stump 17" dia., bears S.71 3/4°W., 98 lks. dist. with healed blaze.  
A Fir 30" dia., bears N.70°W., 96 lks. dist., with healed blaze.  
and a new bearing tree:  
A Yew 11" dia., bears S.71 3/4°W., 116 lks. dist. mkd. T23S R8W S24 BT.

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1336, Surveyed Aug/Oct. 1986 - (DCSO records Vol. 48 Page(s) 18279)

-----

At the sec. cor., monumented with an iron post 2½" dia., firmly set, projecting 4" above ground with the 1964 brass cap, from which the remains of an original bearing tree;  
A rotted Fir snag, size indeterminate, bears N.45°E., 17 lks. dist., no marks visible.  
and the remains of bearing trees mkd. by Brooks and Peterson  
A Fir 17" dia., bears N.34½°E., 27 lks. dist., with healed blaze.  
A Fir 18" dia., bears S.69½°E., 71 lks. dist., with healed blaze.  
A Fir stump, size indeterminate, bears S.71½°W., 98 lks. dist., no marks visible.  
(Cont. Next Page)

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T23-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A Fir 33" dia., bears N.70°W., 96 lks. dist., with healed blaze.  
and a new bearing tree:  
An Alder 11" dia., bears S.23 3/4°W., 77 lks. dist., mkd.  
T23S R8W S24 BT.