

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T23-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 6 Page(s) 2629)

Set a post 40" long, 5" dia., 18" in ground for the cor. to secs. 25, 30, 31 and 36, from which
A Fir 14" dia., bears N.52°E., 10 lks. dist.
A Fir 12" dia., bears S.66°E., 24 lks. dist.
A Fir 24" dia., bears S.46°W., 59 lks. dist.
A Fir 16" dia., bears N.30°W., 23 lks. dist.

Michael S. McDowell - For: Weyerhaeuser Co. - Dec. 1, 1976 - C.S. File 58/128 and M 62-48

Set 2" galv. I.P. with brass cap, from which
A 12" Chinquapin scribed "BT", bears N.57°W., 16.7 ft.
A 10" Chinquapin scribed "BT", bears S.41°E., 9.6 ft.
A 10" Fir scribed "BT", bears S.87°W., 15.2 ft.
A 14" Fir scribed "BT", bears N.35°W., 11.2 ft.

Fd. OK, May 1991 - M 113-34 A & B

Fd. ok on BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor & Richard L. Sanford, Survey Technician, under Group #1709, surveyed Aug. 1993/Feb. 1995 - (DCSO Vol. 52 Page(s) 19659)

Estabrook Land Surveying - For: Weyerhaeuser Co. - 5/1/2025 - M-186-6

Found - 2" Iron pipe with brass cap
14" Fir stump with healed face and tag. Bears N.35°W. 11.2'.
12" Fir stump with tag, bears S.87°W. 15.2'
New - 18" Fir, faced & scribed "SW S30 BT" with X-chop & tag, bears N.32°E 31.0' to spike at side center.
17" Fir, faced & scribed "SW S30 BT" with X-chop & tag bears N.70°E. 32.8' to spike at side center.
13" Fir, faced & scribed "NE S36 BT" with X-chop & tag bears S.47°W 21.8' to spike at side center.
12" Fir, faced & scribed "SE S25 BT" with X-chop & tag bears N.80°W. 33.9' to spike at side center.