

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30; & 25, T23-10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 6 Page(s) 2629)

-----  
Set Hemlock post 40 x 5 for ¼ sec. corner between secs. 25 and 30, 18" in ground, from which  
A Fir 36" dia., bears N.80°E., 13 lks. dist.  
A Fir 40" dia., bears N.50°W., 13 lks. dist.

Clifford A. Stephens - For: Coos Head Timber - Sept. 12, 1957 - C.S. File 42/299

-----  
I find that in the construction of the BLM road, the 2 original BTs had been destroyed. The 3/4" Iron pipe had been bent over, but still in place. I straightened out the pipe and added the "cattle guard" as a B.O. as follows:

The SW. cor. of the concrete cattle guard base bears N.47½°E., 8.8 ft.  
Set 3/4" Iron pipe from 2 orig. BTs as follows:  
A Fir snag, bears N.80°E., 9.5 ft., scribing visible.  
A Fir snag 40" dia., bears N.50°W., 9.1 ft.  
New BTs:  
A Fir 12" dia., bears N.78½°E., 61.2 ft. BLM tag on face also scribed.  
A Fir 16" dia., bears N.56°W., 44.2 ft.

Fd. OK, May 1991 - M 113-34 A & B  
Fd. OK, Aug. 1996 by T. Hostettler - M 126-31

BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor & Richard L. Sanford, Survey Technician, under Group #1709, surveyed Aug. 1993/Feb. 1995 - (DCSO Vol. 52 Page(s) 19660-1)

-----  
The ¼ sec. cor. of secs. 25 & 30, perpetuated Stephens, in 1957, Hintz, in 1975, McDowell, in 1976, Luckman, in 1982, & Ward, in 1991; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, from which bearing trees and bearing object mkd. by Stephens:

A fir, 30 ins. diam., bears N.79 3/4°E., 91½ lks., with healed blaze.  
A fir, 29 ins. diam., bears N.56°W., 66½ lks. dist., with healed blaze.  
The SW. corner of a cattle guard (concrete base) bears N.47½°E., 13½ lks.

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30; & 25, T23-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point  
Set a stainless steel post, 28 ins. long, 2½ ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T23S

¼

R10W R9W

S 25 S 30

1993

Deposit iron pipe and a white "DEEP-1" magnetic marker at  
base of stainless steel post, and a steel fence post  
alongside.