

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19; & 24, T23-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by - William H. Byars, Dep Surveyor Under Contract No. 292, dated 8/7/1878 - (DCSO rec Vol. 6 Page 2630)</p> <p>-----</p> <p>Marked Hemlock 10" dia., for the ¼ sec. corner between secs. 19 and 24, from which</p> <p> A Fir 36" dia., bears S.20°E., 54 lks. dist.</p> <p> A Fir 36" dia., bears S.57°W., 53 lks. dist.</p>
<p>Arnold Gibson - For: Oregon State Board of Forestry - June 29, 1972 - M 47-1</p> <p>-----</p> <p>Set 1½" x 36" galv. Iron pipe with 3" bronze cap mkd. "Ore. St. Bd. of Forestry", 36" in ground, from which</p> <p> 16" Hemlock S.57°E., 42.6 ft. with YMLP mkd. RS 359.</p> <p> 14" Hemlock N.22°W., 30.9 ft.</p> <p> 4" x 4" x 72" white painted Cedar post, N.84°E., 4.0 ft.</p>
<p>Lloyd Smith - For: Oregon State Board of Forestry - Sept. 29, 1981 - M 89-40</p> <p>-----</p> <p>Set OSBF 1½" x 36" galv. I.P. with 3" bronze cap, placed 34" in ground. (OSBF P/C 34" in ground), from which</p> <p> 20" Hemlock bears N.46°W., 21.2 ft., RS.</p> <p> 24" Hemlock bears S.10°E., 25.4 ft., YMLP</p> <p> 4"x4"x72" white painted cedar post, bears N.57°E., 1.8 ft.</p> <p> 5/8" x 30" Iron rod bears N.80°10'58"W., 23.71 ft.</p>
<p>Fd. OK, Nov. 1995 by T. Hoshell - M 123-13</p>
<p>Fd. & used on BLM dependent resurvey by John A. Farmer, Cadastral Surveyor, under Group #1789, surveyed Sept. 1995/Oct. 1995 - (DCSO records Vol. 52 Page(s) 19848)</p>
<p>James McIntosh, State of Oregon, Dept. of Forestry - Tim Van Vleet witness - Ralph C. Hall - 7/ 2005 - C.S. File 65/54-28</p> <p>-----</p> <p>Found - Oregon State Board of Forestry 1½" galvanized IP with 3" bronze cap (in place) from which a:</p> <p> 20" Hemlock N.46°W., 21.2 ft.; now 23" in place, face closed, BLM bearing tree tag.</p> <p> 24" Hemlock S.10°E., 25.4 ft.; now 29" in place, face closed, BLM BT tag & yellow metal location poster</p> <p> 4"x4"x72" White Painted Cedar Post N.57°E., 1.8 ft. missing.</p> <p> 5/8"x30" iron rod N.80°10'58"W., 23.71 ft. in place</p> <p>New - Carsonite witness post S.46°E., 3.40 ft. to base.</p> <p> Carsonite witness post S.58°W., 3.25 ft. to base.</p>