

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T23-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 6 Page(s) 2630)

Set Chitem-wood post 36 x 5, 18" in ground for corner to secs. 13, 18, 19 and 24, from which
A Fir 60" dia., bears N.25°E., 62 lks. dist.
A Maple 6" dia., bears S.25°E., 18 lks. dist.
A Maple 14" dia., bears S.75°W., 14 lks. dist.
A Maple 12" dia., bears N.22°W., 57 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #658 - Surveyed Oct/Nov. 1967 - (DCSO records Vol. 36 Page(s) 14602-03)

The Sec. Cor., determined at intersection of fences extending N., E., and W. This point has been used by local landowners for many years as the corner and is accepted as the best available evidence of the position of the original corner.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:
T 23 S
R 10 W R 9 W
S 13 S 18
S 24 S 19
1967

from which
A Myrtle 8" dia., bears N.69°E., 339 lks. dist. mkd. T23S R9W S18 BT.
A Maple 8" dia., bears N.25°W., 648 lks. dist. mkd. T23S R10W S13 BT.
No other suitable trees available within limits.

Robert W. Ward - For: Champion International Corp. - Nov. 1981 - M 89-63

Found - 2½" BLM brass cap on a 2½" I.P. set in 1967.
8" Myrtle bears N.69°E., 223.7 ft. scribed T23S R9W S18 BT. (1967)
8" dead, down Ash (rec. Maple) bears N.27°W., 427.7 ft. scribing not found. (1967)
New BT - 11" Ash bears N.02°E., 81.3 ft. scribed T23S R9W S18 BT.

Fd. OK, Nov. 1995 by T. Hoshell - M 123-13

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T23-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by John A. Farmer, Cadastral Surveyor,
under Group #1789, surveyed Sept. 1995/Oct. 1995 - (DCSO
records Vol. 52 Page(s) 19848-9)

The cor. of secs. 13, 18, 19 & 24, monumented with an iron
post, 2½" diam., firmly set flush with the ground, with brass
cap mkd.

T23S
R10W R9W
S 13 S 18
S 24 S 19
1967

from which the remains of bearing trees mkd. by Beck

A myrtle, 7" diam., bears N.68½° E., 339 lks., no marks
visible on open decayed blaze. (Record N.69°E.)

a bearing tree not of known record

An ash, 15" diam., bears N.0½°E., 122 lks., with illegible
scribe marks on partially healed blaze.

and a new bearing tree

A twin ash, 6" diam., bears N.89¼°W., 341 lks., mkd. T23S
R10W S13 BT.

No other suitable accessories available.

The corner is located at the intersection of fences which
extend N, E, and W.