

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T23-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 6 Page(s) 2630-31)

Set Fir post 40 x 5, 18" in ground for the ¼ sec. corner between secs. 13 and 18, from which
A Maple 10" dia., bears S.16°E., 100 lks. dist.
A Fir 60" dia., bears N.30°W., 37 lks. dist.

F.J. Cole, Deputy - For: F.L. Newkirk - Nov. 5, 1915 - Vol. 2 Pg. 227

Search for trees and due East, 80 lks., find the Maple called for in original field notes. Set at tree and run N.16°W. and search for original corner stake. Find no evidence of stake or of Fir BT called for in field notes.
SET Fir post 4" x 4" x 4 ft., 2 ft. in ground mkd. CS on North side, S18 on East side and S13 on West side.
Search North for old evidence of line, find numerous blazes. Checking location of stake as being on original line. Line of blazes also corresponds with line of old fence across bottom lands and shows beyond a doubt that the old accepted property line had been very closely maintained on original survey line for a long period of time.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #658 - Surveyed Oct/Nov. 1967 - (DCSO records Vol. 36 Page(s) 14603)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap mkd:
T 23 S
R 10 W R 9 W
¼
S 13|S 18
1967

from which
A Fir 22" dia., bears N.38°E., 66 lks. dist. mkd. ¼ S18 BT
A Hemlock 28" dia., bears N.38°W., 55 lks. dist. mkd. ¼ S13 BT.

From this point, an unrecorded iron pipe, 1" dia., firmly set, protruding 8" above ground, bears N.11°30'W., 0.62 chs. dist.

From this same point, a locally established corner monumented (Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T23-10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

with a wooden hub, 2 x 2 ins., firmly set, protruding 2" above ground, bears S.88°45'W., 0.74 chs. dist., from which
A Fir 43' dia., bears N.40°W., 32 lks. dist. mkd. ¼ S BT on opened blaze. (Annual ring count indicates the blaze to be about 50 years old.)

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2074, surveyed April/June 2004 - (DCSO records Vol. 54 Page(s) 21266)

The ¼ sec. cor. of secs. 13 & 18, on the W. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd from which the bearing trees mkd. by Beck

A fir, 36" dia., bears N.43½°E., 43.6 ft., with a healed blaze. (Record, N.38°E.)

A hemlock, 33" dia., bears N.29¾°W., 36.3 ft., with a healed blaze. (Record, N.38°W.)

and a monument set by person(s) unknown, reported by Beck

An iron pipe, 1" dia., firmly set, projecting 6" above ground, inside of which is an iron rod, 3/8" dia., firmly set, projecting 12" above ground, bears N.11°12'01"W., 42.08 ft. (Rec., N.11°30'W., 40.92 ft.)

From this same point, a point established as the ¼ sec. cor. of secs. 13 & 18 by person(s) unknown, reported by Beck, determined at Beck's record bearing & dist., bears S.88°45'W., 48.84 ft. monument missing, from which a bearing tree mkd. by person(s) unknown, reported by Beck

A fir, 48" dia., bears N.40°W., 26.5 ft., with scribe marks ¼ and other illegible scribe marks visible on open blaze. (Record, 21.1 ft.)