

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 100543

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12, T23-10 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 6 Page(s) 2631)

-----  
Set Chinquapin post 36 x 5, 18" in ground for the ¼ sec. corner between secs. 7 and 12, from which  
A Fir 16" dia., bears N.3°E., 100 lks. dist.  
A Fir 24" dia., bears S.60°E., 38 lks. dist.

Wm. C. Stiles - For: SEEK, Inc. - Sept. 13, 1968 - C.S. File 55/89 and M 36-42

-----  
Set 2½" brass cap mkd.       SEEK, Inc.  
                                  T 23 S   R 10 W  
                                  ¼ S 12 |  
                                  1968 |  
New BTs- 30" Fir, N.18°W., 28.0 ft. mkd. ¼ S12.  
          36" Fir, S.78°W., 19.7 ft. mkd. ¼ S12.

FD. BC & BTs by W. Barnes - 5/1974 - C.S. file 55/341-3

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23214-5)

-----  
The ¼ sec. cor of sec 12 only, reestablished by proportionate measurement by Stiles, in 1968. There is no remaining evidence of the original cor. and this position is accepted as a careful and faithful reestablishment of the cor.; monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Stiles  
A fir, 39" dia., bears S.80°W., 21.0 ft., with a healed blaze at waist height.  
A fir stump, 37" dia., bears N.19¼°W., 28.9 ft., with a healed blaze at waist height.  
and a new bearing tree  
A hemlock, 18" dia., bears N.7½°W., 48.4 ft. mkd. ¼ S12 BT  
From this cor., S.1°33'40"E., 295.44 ft., to a point on the line bet. secs. 7 & 12; from this point, a point established, by person(s) unknown bears E., 3.58 ft., and is not utilized in this survey; monumented with an iron rod, 30" long, 5/8" dia., lying loosely on a collar of stone.  
Also from this same corner, S.1°33'40"E., at:  
190 ft., top of rock face, slopes S.  
375 ft., bottom of rock face.

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 100543

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12, T23-10 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new bearing tree has a 2½"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.