

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Arnold Gibson - For: Oregon State Board of Forestry
Marcy 15, 1968 - M 36-32

Set Ore. St. Bd. of Forestry 1½" x 36" galv. I.P. with bronze
cap., from which
24" Fir N.62 3/4°W., 38.5 ft. (¼ S6 BT)
21" Fir S.80°E., 28.4 ft.
25" Fir S.27½°E., 31.4 ft. (RS 359) with yellow metal
location poster.
Ridge top, course NE., South 65.0 ft.
White painted Cedar post bears N.E. 1.0 ft.

Arnold G. Gibson, Oregon St. Board of Forestry - Ed Kucera,
D. Smith, G. Gresham, W. Cook, & R. Ball - 7/1968 - M 36-32

Set - Oregon St. Bd. of Forestry 1½"x36" galv. IP eoyj 3
bronze cap, 34" in the ground.
24" Fir N.62 3/4°W., 38.5 ft. (¼ S6 BT)
21" Fir S.80°E., 28.4 ft.
25" Fir S.27½°E., 31.4 ft. (RS359) Yellow metal
location poster
Ridge top, course NE, south 65.0 ft.
White post Cedar post 4"x4"x72" NE 1.0 ft.

BLM resurvey by James E. Jelley and Rolla R. Steward,
Cadastral Surveyors under Group # 703, surveyed July 1969/May
1970 (DCSO records Vol. 35 Page(s) 14551)

(1968 OSBF cap and 3 BTs found OK)
The corner point is located on top of spur ridge, bears NW.
and SE.