

PRIMARY CORNER DESCRIPTION 1/4 Cor. 30 & 31

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2633)

-----  
Set Fir post 5 ft. long, 5" dia., 20" in ground for the sec. cor. between secs. 30 & 31, from which  
A Fir, 10" dia., bears N.28°E., 12 lks.  
A Chinquapin, 10" dia., bears S.10°W., 18 lks.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Perron - June 1970 - C.S. File 54/60-53

-----  
Found - Orig. 10" now 16" Fir snag, N.28°E., 7.9 ft., "¼" scribe visible on open blaze.

No trace of other OBT.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R9W  
OFFICE 1970 S 30  
S 31

8" Chinquapin N.85°E., 7.6 ft. mkd: "¼ S30 CS BT"  
(No other suitable trees in Sec. 30)

32" D.Fir S.42°W., 22.9 ft., mkd: ¼ S31 CS BT

This corner lies on top of spur, sloping NW & in extremely dense brush. No best way to go to this corner at this time.

Fd. OK 5/1991 - M 113-34 A&B

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16226)

-----  
The ¼ sec. cor. of secs. 30 & 31, perpetuated & rec. by Douglas Co. Surveyor, in 1970, monumented with an iron post, 2" dia., firmly set, projecting 4" above ground, with properly mkd. brass cap.

from which the remains of an OBT

A sawed Fir stump, 16" dia., bears N.28°E., 12 lks., with scribe marks ¼ S visible on partially healed blaze.

and the remains of BTs mkd. by the County Surveyor

A Chinquapin snag, 8" dia., bears N.85°E., 13 lks., with scribe marks BT visible on partially healed blaze.

A sawed Fir stump, 34" dia., bears S.42°W., 36 lks., with healed blaze.

and a new BT

A Fir, 8" dia., bears N.33¼°W., 87½ lks., mkd: ¼ S30 BT.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor & Richard L. Sanford, Survey Technician, under Group #1709, surveyed Aug. 1993/Feb. 1995 - (DCSO Vol. 52 Page(s) 19661-2)

-----

From the 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

County Surveyors Office  
T23S  
S 30  
S 31  
R9W  
1970

from which the remains of an original bearing tree  
A fir stump, 12" diam., bears N.28°E., 12 lks., no marks visible on a badly decayed blaze.  
and the remains of bearing trees mkd. Tracy, in 1970, reported by Bowder  
A chinquapin, size indeterminate, bears N.85°E., 13 lks., no marks visible on a badly decayed blaze.  
A fir stump, 28" diam., bears S.39°W., 36 lks., with healed blaze. (Record, S.42°W.)  
and the remains of a bearing tree mkd. by Bowder  
A roothole, bears N.33¼°W., 87½ lks., with a downed fir alongside, 10" diam., with healed blaze.  
and new bearing trees  
A hemlock, 9" diam. bears N.82½°E. 40½ lks., mkd. ¼ S30 BT  
A fir, 5" diam., bears S.28¼°E., 58½ lks., mkd. ¼ S31 BT.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23310-11)

-----

The ¼ sec. cor. of secs. 30 & 31, monumented with an iron post, 1" dia., firmly set, projecting 9" above ground, with a brass cap (properly) mkd.  
from which the remains of an original bearing tree  
A decayed fir stump, size indeterminate, bears N.28°E., 7.9 ft., no marks visible.  
and the remains of a BT mkd. by the Douglas County Surveyor's Office in 1970  
A decayed fir stump, 32" dia., bears S.39°W., 23.8 ft., no marks visible.

and the remains of a bearing tree mkd. by Bowder in 1977

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. 30 & 31

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

A root hole bears N.33¼°W., 57.8 ft., alongside of which is a down decayed fir, 10" dia., with the remains of a healed blaze.

and the bearing trees mkd. by Peterson and Sanford in 1993-95

A hemlock, 15" dia., bears N.82½°E., 26.7 ft., with scribe marks BT and other illegible scribe marks visible on partially healed blaze.

A fir, 12" dia., bears S.29¾°E., 38.6 ft., with a healed blaze. (Record, S.28¼°E.)

Drive an aluminum angle iron alongside the cor.