

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2634-5)

-----  
Set a Myrtle post, 5 ft. long, 5" dia., 20" in the ground for the 1/4 sec. cor. bet. secs. 19 & 30 from which

A Fir, 24" dia., bears S.50°W., 38 lks.

A Fir, 24" dia., bears N.45°W., 15 lks.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16226-7)

-----  
Point for 1/4 sec. cor. of secs. 19 & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T23S R9W  
1/4     S 19  
          S 30  
1977

from which

A Fir, 10" dia., bears N.24°W., 72 lks., mkd: 1/4 S19 BT.

A Fir, 6" dia., bears S.23 1/2°E., 39 1/2 lks., mkd: 1/4 S30 BT.

Fd. of 5/1991 M 113-34 A & B

BLM dependent resurvey by Boyd W. Peterson, Cadastral Surveyor & Richard L. Sanford, Survey Technician, under Group #1709, surveyed Aug. 1993/Feb. 1995 - (DCSO Vol. 52 Page(s) 19664)

-----  
The 1/4 sec. cor. of secs. 19 & 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5" above ground, with brass cap mkd.

T23S R9W  
1/4     S 19  
          S 30  
1977

from which bearing trees mkd. by Bowder

A fir, 13" diam., bears S.23 1/2°E., 39 1/2 lks., with healed blaze.

A fir, 15" diam., bears N.24°W., 70 1/2 lks., with healed blaze. (Record, 72 lks.)