

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Robert W. Ward - For: Champion International Corp. - Nov. 1981 - M 89-63

Set - 2½" brass cap on a 2½" x 30" iron pipe extending 6" above ground.

14" Fir bears S.60°W., 11.8 ft. (1981)

11" Fir bears N.8°E., 6.8 ft. (1981)

Both BTs scribed C ¼ S18 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2074, surveyed April/June 2004 - (DCSO records Vol. 54 Page(s) 21262)

The center ¼ sec. cor. of sec. 18, established by Ward, in 1981, & is accepted as the corner, monumented with an iron pipe, 2" dia., firmly set, projecting 9" above ground, with brass cap mkd.

T 23 S R 9 W

S 18 C ¼

1981

PLS 1091

from which the remains of the bearing trees mkd. by Ward

A fir, 16" dia., bears N.1½°E., 6.7 ft., with a healed double blaze.

A fir snag, 17" dia., bears S.53¼°W., 11.4 ft., with a healed double blaze.

and a new bearing tree

A fir, 23" diam., bears S.76¾°E., 15.2 ft., mkd. C¼ S18 BT
Corner is on the NE. cor. of logged area, edge bears S. and W.; a steel fence post is alongside.

Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.