

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #279, dated March 5, 1878 - (DCSO records Vol. 4 Page(s) 1648)

Set a Hemlock post 5" dia., 40" long, 20" in ground, for the ¼ sec. corner, from which,

A Fir 20" dia., bears North, 18 lks. dist.

A Fir 24" dia., bears South, 23 lks. dist.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #688, dated June 9, 1898 (DCSO records Vol. 7 Page(s) 2697)

We look for ¼ sec. cor. and its witness trees in this neighborhood, but must have passed the same.

Arnold G. Gibson - For: Ore. State Bd. of Forestry - Oct. 26, 1967 - C.S. File 55/68-6

Found - Original post, now missing, from which a 20" Fir bears North, 18 lks., now 26", face opened, knife scribes 4S visible at correct age.

24" Fir bears South, 23 lks., now 28" snag, knife scribes 1/ - S BT visible at correct age.

Creek, course N., bears East 325 lks., now in place.

Set 1½" x 36" galv. iron pipe with 3" brass cap mkd: "Ore. St. Bd. of Forestry ¼ S31 S6 1967 RS359", 30" in ground, from which a

20" Hemlock bears S.69½°W., 42.2 ft. to face, scribed ¼ S6 BT RS359.

Set 4"x4"x72" white painted cedar post 1.2 ft. S. of corner pipe.

Fd. OK, Jan. 1968, DCSO, J. Byron - C.S. File 54/60-24

BLM resurvey by James Jelley and Rolla Steward, Cadastral Surveyors, under Group #703, surveyed July 1969/May 1970 - (DCSO records Vol. 35 Page(s) 14548)

(Corner Report)

The ¼ sec. cor., perpetuated and recorded by the OSBF in 1967, monumented with an iron post 1½" dia., firmly set, projecting 6" above ground, with 1967 brass cap, from which the original bearing trees:

A Fir 30" dia., bears N.4°W., 20½ lks. with frag. scribe marks visible on open blaze. (Rec. North, 18 lks.)

A Fir snag 30" dia., bears S.9½°E., 25 lks. dist. with fragmentary scribe marks visible on open blaze. (Rec. South, 23 lks.)