

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2634)

Set Dogwood post 5 ft. long, 5" dia., 20" in ground for the corner to secs. 19, 20, 29, & 30, from which:

- A Fir, 60" dia., bears N.20°E., 51 lks.
- A Fir, 60" dia., bears S.10°E., 11 lks.
- A Fir, 24" dia., bears S.15°W., 12 lks.
- A Fir, 50" dia., bears N.45°W., 38 lks.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16217-8)

Point for the cor. of secs. 19, 20, 29, & 30, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground, with brass cap marked:

T23S R9W
S 19|S 20
S 30|S 29

from which

- A Fir, 10" dia., bears N.42 3/4°E., 22 lks., mkd: T23S R9W S20 BT.
- A Fir, 18" dia., bears S.79°E., 45 lks., mkd: T23S R9W S29 BT.
- A Fir, 15" dia., bears S.22¼°W., 9 lks., mkd: T23S R9W S30 BT.
- A Fir, 15" dia., bears N.33½°W., 26 lks., mkd: T23S R9W S19 BT.