

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2635)

Set Willow post, 5 ft. long, 5" dia., 20" in the ground for the sec. cor. between secs. 19 & 20, from which:
A Fir, 24" dia., bears S.65°W., 60 lks.
A Willow, 5" dia., bears S.50°E., 16 lks.

Arthur R. Evans - Wit: J.I. Clinton and Elvin DeGrath - Feb. 25, 1952 - C.S. File 41/6-2 & 41/25

Location determined by testimony of A.O. Gustafson, who has seen orig. stake in place.
Set - 1" iron pipe for corner, blazed & scribed BT:
10" Alder S.60°E., 60.5 ft.
12" Alder N.50°E., 25.0 ft.
No suitable trees in Sec. 19

BLM Dependent resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14558-9)

From the ¼ sec. cor. of secs. 19 & 20, determined at record bearing & dist. from a BT marked & recorded by Evans in 1951. Evans determined the corner position by testimony of A.O. Gustafson, an interested land owner, who had knowledge of the orig. corner position & BTs.
from which Evans BT
An Alder, 20" dia., bears N.50°E., 38 lks., with scribe marks ¼ S20 R visible on bark.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T23S R9W
¼
S 19|S 20
1969
from which new BTs
A Fir, 26" dia., bears S.51°E., 210 lks., mkd: ¼ S20 BT.
A Fir, 19" dia., bears S.11°W., 235 lks., mkd: ¼ S19 BT.

Fd by DCSO - Vernon "Ray" Tracy - July 1970 - C.S. File 54/60

Fd. & used on BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16228)

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by John A. Farmer, Cadastral Surveyor, under Group #1789, surveyed Sept. 1995/Oct. 1995 - (DCSO records Vol. 52 Page(s) 19849)

From the ¼ sec. cor. of secs. 19 & 20, monumented with an iron post, 2½" diam., firmly set, projecting 4" above ground, with properly marked brass cap from which the remains of bearing trees mkd. by Jelly and Steward
A fir, 34" diam., bears S.51°E., 210 lks., with healed blaze.
A fir snag, 24" diam., bears S.10°W., 235 lks., with healed blaze. (Record S.11°W.)
and a new bearing tree
A fir, 20" diam., bears S.19¼°W., 256½ lks. mkd. ¼ S19 BT.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23311-12)

The ¼ sec. cor. of secs. 19 & 20, monumented with an iron post, 2½" dia., firmly set, with top flush with the surface of the ground, with a brass cap (properly) mkd. from which the remains of the BTs mkd. by Jelley and Steward in 1969-70
A fir, 40" dia., bears S.51°E., 138.6 ft., with a healed blaze.
A fir snag, 23" dia., bears S.10°W., 155.1 ft., with a healed blaze at breast height.
and a bearing tree mkd. by Farmer in 1995
A fir, 24" dia., bears S.19¼°W., 169.3 ft., with a healed blaze.
A steel fence post is alongside the cor.
Corner is located in an open field.
From the corner
S., 30 ft., cor. of barbed-wire fences, with fence lines extending N. and N.75°W.
NAD 1983 (2011)
Latitude: 43°33'05.66"N Longitude: 123°47'51.26"W