

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2635)

-----  
Set a Maple post, 5 ft. long, 5" in dia., 20" in the ground for the corner to secs. 17, 18, 19, & 20, from which  
An Alder, 5" dia., bears N.85°E., 15 lks.  
An Alder, 24" dia., bears S.20°E., 56 lks.  
An Ash, 24" dia., bears S.88°W., 80 lks.  
A Maple, 6" dia., bears N.18°W., 13 lks.

BLM Dependent resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14559)

-----  
Point for the cor. of secs. 17, 18, 19, & 20, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground, with brass cap marked:

T23S R9W  
S 18 | S 17  
S 19 | S 20  
1969

from which  
An Alder, 7" dia., bears N.17°E., 37½ lks., mkd: T23S R9W S17 BT on bark blaze.  
An Alder, 9" dia., bears S.64½°E., 40 lks., mkd: T23S R9W S20 BT on bark blaze.  
An Alder, 6" dia., bears S.23°W., 41 lks., mkd: T23S R9W S19 BT on bark blaze.  
An Alder, 7" dia., bears N.74 3/4°W., 40½ lks., mkd: T23S R9W S18 BT on bark blaze.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23312-3)

-----  
The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2½" dia., firmly set, projecting 1" above ground, with a brass cap (properly) mkd.

from which the bearing trees mkd. by Jelley and Steward in 1969-70  
An alder, 19" dia., bears N.13°E., 23.8 ft., with scribe marks BT and other illegible scribe marks visible on bark. (Record, N.17°E., 24.8 ft.)  
An alder, 16" dia., bears S.64½°E., 25.6 ft., with scribe marks T23S R9W S20 BT visible on bark. (Rec, 26.4 ft) and a new bearing tree  
An alder, 9" dia., bears S.33°W., 22.1 ft., mkd. T23S R9W S19 BT on bark. continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

There are no new BTs available within limits in sec. 18.  
Drive an aluminum angle iron alongside the cor.  
Corner is located on the E. edge of an open field, edge bears  
N. and S.45°W.