

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2623)

-----

Set Fir post 4 ft. long, 4" dia., 20" in ground for ¼ sec. corner, from which

- A Fir, 48" dia., bears N.65°E., 46 lks.
- A Fir, 48" dia., bears S.80°W., 36 lks.

Arnold G. Gibson - For: Ore. State Bd. of Forestry - Oct. 26, 1967 - C.S. File 55/68-5

-----

Found - Post, now missing, from which

- 48" Fir bears N.65°E., 46 lks., now 48" Fir, orig. bark scribes "¼ S BT" visible.
- 48" Fir bears S.80°W., 36 lks., now 60" windfall.

Set - 1½"x36" galv. iron pipe with 3" brass cap mkd: "Ore. St. Bd. of Forestry ¼ S6 S5 1967 RS 359" 34" in ground, and from which

- 14" Hemlock bears N.16°W., 1f8.0 ft., to face scribed ¼ S6 BT.
- 13" Hemlock bears S.86°E., 26.0 ft., to face; scribed "¼ S5 BT"
- 4" x 4" x 72" white painted Cedar post 1 ft NW of corner pipe. Ore. St. Forestry Dept. metal location poster on the 14" BT

Fd & used on BLM Dependent resurvey by James E Jelley & Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14568)

Ron Quimby - Crew: N. Fromdahl & R Heichel - 12/2018 - C.S. File 65/102-13

-----

Found - 1967 brass cap missing.

- 48" Fir stump open scar N.65°E., 30.4 ft tagged.
- 13" decayed hemlock S.86°E., 26.0 ft tagged

Set - 2½" alum. Cap on 5/8"x30" I.Rod at interest of distance from fd. BTs. Cap mkd: ROSEBURG RESOURCES COMPANY ¼ S6•S5 LS 1654 2018

New - 14" Fir N.20°E., 13.5 ft. scribe ¼ S5 BT.

- 9" Fir S.72°E., 8.5 ft. scribed ¼ S5 BT.
- 4" Fir S.18°W., 14.7 ft. scribed ¼ S6 BT.
- 4" Fir N.48°W., 12.6 ft. scribed ¼ S6 BT.

Note - Compass decl. 15½°E.