

PRIMARY CORNER DESCRIPTION Cor. Secs. 7 & 8, North bdy

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2622)

-----

Set a Fir post 5" dia., 4 ft. long, 20" in ground for the corner to secs. 5, 6,7, & 8, from which

- A Hemlock, 14" dia., bears N.87°E., 58 lks.
- A Hemlock, 24" dia., bears S.65°E., 80 lks.
- A Fir, 48" dia., bears S.82°W., 138 lks.
- A Hemlock, 48" dia., bears N.72°W., 84 lks.

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2656)

-----

At the cor. of secs. 5, 6,7 & 8, I destroyed all marks referring to secs. 7 & 8, I set an Alder post, 3 ft. long, 4" sq. 24" in the ground, for closing cor. of secs. 7 & 8, marked CC T23S R9W on S; S8 on E and S7 on W faces with 5 grooves on E & S faces from which

- A Fir, 40" dia. bears S.32°E., 57 lks. mkd: T23S R9W S8 BT
- A Fir, 30" dia. bears S.63°W., 60 lks. mkd: T23S R9W S7 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Perron - June 1970 - C.S. File 54/60-52

-----

Reported as not found.  
 No trace of OBTs, we do find 2 Fir trees with "X"s & Brag mks in the approx. corner location.

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23222)

-----

Point for the closing cor. of secs. 7 & 8, on the S. bdy. of sec. 5, at proportionate; there is no remaining evidence of the original cor.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 23 S R 9 W
S 5
S 7   S 8
C C
2014

from which new bearing trees

- A fir, 43" dia., bears S.38½°E., 23.6 ft., mkd. T23S R9W S8 CC BT.
- A fir, 13" dia., bears S.63°W., 41.1 ft., mkd. T23S R9W S7 CC BT.

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 233600

PRIMARY CORNER DESCRIPTION Cor. Secs. 7 & 8, North bdy

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new bearing tree has a 2½"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.