

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2654)

Set a Fir post, 3 ft. long, 3" sq. 24" in the ground for 1/4 sec. cor. mkd: 1/4 S29 on N face and 32 on S face, from which:
 A Fir, 30" dia., bears S.79°W., 33 lks., mkd: 1/4 S32 BT.
 A Fir, 20" dia., bears N.76°W., 37 lks., mkd: 1/4 S29 BT.

Louis Prahar - For: Weyerhaeuser Co. - June 8, 1966 - C.S.File 55/11

Found - Fir windfall with bark scribes. Orig. 1898 Fir BT, 30" dia., now 36", bears S.79°W., 21.8 ft. from 1/4 cor.
 The orig. 20" BT. Fir not identifiable from other windfalls.

Set - 5/8" rod for 1/4 cor. from orig. position of the standing tree, located south, facing slope.
 17" Chinquapin N.18°43'W., 23.57 ft. to notch w/spike. Weyerhaeuser metal tag.
 17" Chinquapin S.14°52'W., 20.7 ft. to spike, Weyerhaeuser metal tag.

Fd. Ok by Douglas Co. Surveyors Office - Vernon "Ray" Tracy - June 1970 - C.S. File 54/60-56

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16224-5)

The 1/4 sec. cor. of secs. 29 & 32, perpetuated & recorded by Prahar in 1966, monumented with an iron rod, 5/8" dia., firmly set, projecting 24" above ground, from which the remains of the OBT:
 A root hole, bears S.79°W., 33 lks., with a down Fir alongside, 36" dia., no marks visible.
 and the remains of BTs mkd. by Prahar
 A Chinquapin, 17" dia., bears N.21 3/4°W., 38 lks., with a steel spike at base.
 A Chinquapin, 20" dia., bears S.15°W., 33 lks., with a steel spike at base.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T23S R9W
 1/4 S 29
 S 32
 1977

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

from which a new BT

A Fir, 5" dia., bears S.46½°E., 61 lks., mkd: X BT.