TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2637-8)

Set Hemlock post 5 ft. long, 5" in dia., 20" in ground for the ¼ sec. cor. between secs. 20 & 29, from which
A Maple, 24" dia., bears N.45°E., 24 lks.
A Hemlock, 20" dia., bears S.40°W., 42 lks.

Fd. & used on GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2647)

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16217)

The ¼ sec. cor. of secs. 20 & 29 determined at the record bearing & distance from the remains of the orig. BTs:
A sawed Maple, 34" dia., bears N.45°E., 24 lks., with axe marks visible on decayed blaze.
A root hole, bears S.40°W., 42 lks.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: T23S R9W

¼ S 20 / S 29

1977

from which new BTs
A Hemlock, 8" dia., bears N.14½°E., 99 lks. mkd: ¼ S20 BT.
A Hemlock, 11" dia., bears S.36°W., 87 lks. mkd: ¼ S29 BT.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23311)

The ¼ sec. cor. of secs. 20 & 29, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd.
from which the remains of an original bearing tree
A maple stump, 34" dia., bears N.45°E., 15.8 ft., no marks visible and maple sprouts up to 19" dia.
and a bearing tree mkd. by Bowder in 1977
A hemlock, 25" dia., bears N.14½°E., 65.3 ft., with a healed blaze.
and a new bearing tree
A hemlock, 20" dia., bears S.66½°E., 24.9 ft., mkd. S29 BT
Drive an aluminum angle iron alongside the cor.