

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Nick Juliano - For: Weyerhaeuser Co. - May 1979 - M 77-50  
-----

Set - 2" x 42" IP  
11" Fir, S.18°E., 55.5 ft. scribed.  
11" Fir, N.37°W., 48.9 ft. scribed.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23315-16)  
-----

The center ¼ sec. cor. of sec. 20, established by Juliano, in 1979, and is accepted as the cor.; monumented with an iron pipe, 42" long, 2" dia., firmly set, projecting 10" above ground, from which the remains of the BTs mkd. by Juliano

A fir, 31" dia., bears S.19½°E., 55.2 ft., with a healed blaze.

A fir stump, 27" dia., bears N.37¾°W., 49.3 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 23 S R 9 W  
C ¼ S 20  
2014

and a new bearing tree

A maple, 13" dia., bears N.8°W., 138.6, mkd. C¼ S20 BT on bark.

Drive an aluminum angle iron alongside the cor.

Remove iron pipe from area.

From the corner

N., 30 ft., centerline of Soup Creek Road, asphalt surfaced, 22 ft. wide, bears N.25°W. and S.40°E., at a cattle guard.