

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Closing Cor Secs 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2646)

Set a sandstone, 16 x 12 x 8 ins., 11" in the ground for cor. of secs. 28, 29, 32, & 33, mkd. with 1 notch(es) on S a(s)nd 4 notch(es) on E edges; from which,
A Yew, 6" dia., bears N.76½°W., 37 lks., mkd: T23S R9W S29 BT.
A Fir, 24" dia., bears S.69°W., 23 lks., mkd: T23S R9W S32 BT.
A Fir, 8" dia., bears N.46°E., 193 lks., mkd: T23S R9W S28 BT.
A Vine-Maple, 5" dia., bears S.73°E., 132 lks., mkd: T23S R9W S33 BT.

GL0 survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2652-3)

I set a Chittewood post, 3 ft. long, 4" sq. 24" in the ground for closing cor. of secs. 28 & 33, marked CC T23S R9W on E. S28 on N.; and S33 on S. faces, with 1 groove on S & 4 grooves on E. faces, from which
A Chittewood, 6" dia., bears N.52°E., 27 lks., mkd: T23S R9W S28 BT.
A Fir, 30" dia., bears S.11°E., 48 lks., mkd: T23S R9W S33 BT.
I destroy all marks on former cor. referring to secs. 28 & 33

Louis Prahar - For: Weyerhaeuser Co. - June 8, 1966 - C.S. File 55/11-1

Set closing corner from orig. Fir BT now a windfall lying northeasterly - originally 30" dia., now 34", bearing S.11°E., 31.68 ft. from CC. Found scribes on bark, bearing & dist. taken from where the tree originally stood.
Set - 5/8" rod - 3 ft. high from orig. BT.
A cut Fir stump 29" dia., bear. & dist. to spike in notch, Weyer. metal tag. N.15°34'E., 35.32 ft.
A cut Fir stump 4 ft. dia., S.5°42'W., 30.82 ft., bear. & dist. to spike in notch. Weyer. metal tag.

Fd ok by Douglas Co. Surveyors Office - Vernon "Ray" Tracy - June 1970 - C.S. File 54/60-56

continued next page

1

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Closing Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Larry E. Monrean - P. Earle -
C.S. File 56/49-6 - 10/25/1973 & Gary L. Langlitz - P. Earle
- C.S. File 56/49-6 - 3/20/1974

10/25/1973

Found - Badly burned stump out of ground, lying
northeasterly. No scribing visible. Orig.
position S.11°E., 31.7 ft.

5/8" iron rod 3.0 ft. high.

Fir stump, 29" dia., bearing & dist. to spike in
notch, N.15½°E., 35.3 ft.

Fir stump, 4 ft., dia., bearing & dist. to spike in
notch, S.4½°W., (rec. S.5°42'W.) 30.8 ft.

Set - Brass cap at closing corner mkd:

COUNTY SURVEYORS T23S R9W
OFFICE

S|28

S29 S|33 CC

No new BTs set (no living trees near) Corner lies
approx. 150 ft. west of cutting line in sec. 29
& 100 ft. south to foot of westerly ridge.

A dead Fir, 28" dia., N.89°E., 47.9 ft., is approx.
150 ft. high.

3/20/1974

Marked brass cap with a "CC" on the closing section line
between Sec. 28 & Sec. 33, also set steel fence post with
survey marker sign attached 1.0 ft. north of corner on this
date.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor,
under Group #927, surveyed Aug. thru Nov. 1977 - (DCS0
records Vol. 41 Page(s) 16221)

S.88°24'W., 38.60 chs

The orig. closing cor. of secs. 28 & 33, perpetuated &
recorded by Prahar in 1966, when orig. evidence was still in
existence, and further perpetuated by the DCS0 in 1973,
monumented with an iron post, 1" dia., firmly set, projecting
12" above ground, with properly marked brass cap.

from which the remains of BTs mkd. by Prahar

A sawed Fir stump, 29" dia., bears N.15½°E., 53 lks., with
an iron spike driven in base.

A sawed Fir stump, 48" dia., bears S.4½°W., 47 lks., with
an iron spike driven in base.

38.67

True point for the closing cor. of secs. 28 & 33.

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Closing Cor. Secs. 28 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap marked:

T23S R9W
S 29 | $\frac{S 28}{S 33}$ CC

from which

A Fir, 4" dia., bears N.78°E., 39½ lks., mkd: X BT.

A Fir, 3" dia., bears S.25½°E., 29½ lks., mkd: X BT.

From this point, the cor. of secs. 29 & 32 only, bears
S.1°27'E., 2.11 chs.

Tony Hostetter - For: Weyerhaeuser Co. - Dec. 2011 - C.S.
File 65/76-10

Found - 1977 BLM brass cap & both BTs as described (in Vol.
41) Pg 16221 Douglas Co. records.

1973 Douglas Co. Surveyor Brass cap bears
S.88°04'E., 4.59 ft.

New BTs- 20" Fir, scribed "S28 SW BT" WEYCO tag, bears
N.61°13'E., 25.2 ft. to spike in root collar.