

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 300235

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 29 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2647)

Set a Hemlock post, 3 ft long, 3" sq. 24" in the ground for ¼ sec. cor., mkd: ¼ S28 on E face, from which

A Vine-maple, 5" dia., bears S.24°E., 8 lks., mkd: ¼ S28 BT.

A Hemlock, 10" dia., bears N.75°W., 53 lks., mkd: ¼ S29 BT.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16218-9)

Point for ¼ sec. cor. of sec. 29 only, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T23S|
R9W|
¼ S29|
1977

from which

A Fir, 8" dia., bears S.42½°W., 52½ lks., mkd: ¼ S29 BT.

A Fir, 9" dia., bears N.63°W., 11½ lks., mkd: ¼ S29 BT.