

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 28 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16219)

-----  
Point for ¼ sec. cor. of sec. 28 only, at proportionate distance.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T23S  
R9W  
¼ S28  
1977

from which

- A Fir, 6" dia., bears N.32½°E., 52½ lks., mkd: X BT.
- A Fir, 10" dia., bears S.53½°E., 49 lks., mkd: ¼ S28 BT.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23307-8)

-----  
The ¼ sec. cor. of sec. 28 only, on the E. bdy. of sec. 29, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd. from which the remains of the BTs mkd. by Bowder in 1977

A root hole bears N.32½°E., 29.6 ft., alongside of which is a down decayed fir, 12" dia., no marks visible. (Record, 34.7 ft.)

A fir, 25" dia., bears S.53½°E., 27.1 ft., with a healed blaze. (Record, 32.3 ft.)

and a new bearing tree

A fir, 30" dia., bears N.43¾°E., 39.7 ft., mkd. X BT.

Drive an aluminum angle iron alongside the cor.