

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 300360

PRIMARY CORNER DESCRIPTION N 1/16 Cor. East Line Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A. R. Evans - Nov. 1951 - C.S. File 41/25

-----  
Set - 3/4" Iron pipe, from which  
An 18" Maple bears N.60°W., 25.8 ft.  
A 16" Hemlock bears S.60°W., 231 ft.  
Marked N 1/16 sec. 20 BT.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor,  
under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO  
records Vol. 41 Page(s) 16213)

-----  
The N 1/16 sec. cor. of sec. 20 only, established and  
recorded by Evans in 1951, when the ¼ sec. cor. of sec. 20  
only was still in existence, determined from the remains of  
BTs marked by Evans:

A Hemlock, 19" dia., bears S.60°W., 35 lks., with scribe  
marks 20 visible on open blaze.

A Maple snag, 18" dia., bears N.60°W., 39 lks., with  
scribe marks 1/16 S visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with  
brass cap marked:                   N 1/16|  
  S 20|  
  1977

from which new BTs

A Hemlock, 9" dia., bears S.43°W., 129 lks., mkd: N 1/16  
S20 BT.

A Hemlock, 15" dia., bears N.64°W., 73½ lks., mkd: N 1/16  
S20 BT.