

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2622)

Set a Maple post, 4 ft. long, 4" sq., 18" in the ground, for cor. to secs. 4, 5, 8 & 9.

- A Fir, 40" dia., bears N.35°E., 32 lks.
- A Fir, 48" dia., bears S.25°E., 26 lks.
- A Fir, 30" dia., bears S.37°W., 58 lks.
- A Fir, 30" dia., bears N.45°W., 75 lks.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Dec. 1967 - C.S. File 54/60-16

Found - Orig. 40" now 50" Fir, alive, N.35°E., 21.1 ft., shows "T2 S" bark scribe in poor condition.
Other BTs turned out.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R9W
OFFICE S 5 | S 4
S 8 | S 9

- 18" Hemlock N.79°E., 10.0 ft. mkd: T23S R9W S4 CS BT
 - 16" Alder N.35°W., 15.2 ft., mkd: T23S R9W S5 CS BT
 - 15" Alder S.53°E., 23.2 ft., mkd: T23S R9W S9 CS BT
- No suitable trees to SW. This corner lies 75 East of creek, course N.

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23221)

The cor. of secs. 4, 5, 8, & 9, perpetuated by the Douglas County Surveyor's Office, in 1968; monumented with an iron post, 1½" dia., firmly set, projecting 11" above ground, with a brass cap (properly) mkd.

from which the remains of an original bearing tree
A fir stump, 55" dia., bears N.35°E., 21.1 ft., with no marks visible.

and a BT mkd. by the Douglas County Surveyor's Office
A hemlock, 30" dia., bears N.78½°E., 9.5 ft., with a healed blaze.

and new bearing trees
A hemlock, 19" dia., bears S.69°E., 34.4 ft., mkd. T23S R9W S9 BT.

A pistol-butt hemlock, 23" dia., bears S.54½°W., 17.9 ft., mkd. T23S R9W S8 BT.

A hemlock, 25" dia., bears N.82°W., 40.7 ft., mkd. T23S R9W S5 BT.

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new bearing tree has a 2½"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.