

PRIMARY CORNER DESCRIPTION SW Cor Sec. 21 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2638)

Set a Cedar post 5 ft. long, 5" in dia., 20" in ground for the corner to secs. 20, 21, 28 & 29, from which,

- A Hemlock, 12" dia., bears N.45°E., 5 lks.
- A Fir, 8" dia., bears S.35°E., 23 lks.
- A Fir, 8" dia., bears S.18°W., 29 lks.
- A Fir, 16" dia., bears N.25°W., 11 lks.

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2682)

Intersect E bdy. of sec. 20, 4.52 chs. N of cor. of secs. 20, 21, 28, & 29 which is a cedar post, 5" sq., 30" above ground, marked and witnessed as described by the surveyor general. I destroy all marks on cor. & witness trees, except those referring to sec. 20.

At the point of intersection, I set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 21 & 28, marked, CC T23S R9W on E; S21 on N, and S28 on S faces, with 4 grooves on E and 2 grooves on S faces from which

- A Fir, 28" dia. bears N.82°E., 17 lks. mkd:T23S R9W S21 BT
- A Fir, 16" dia. bears S.11°E., 32 lks. mkd:T23S R9W S28 BT

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16215-6)

7.98 chs., West

The orig. closing corner of secs. 21 & 28, determined at record bearing & dist. from the remains of the orig. BTs:

- A sawed Fir stump, 30" dia., bears N.82°E., 17 lks., with scribe marks T23S R9W S21 visible on opened blaze.
- A sawed Fir stump, 18" dia., bears S.11°E., 32 lks., with illegible scribe marks visible on partially opened blaze.

8.29 chs.

True point for the closing cor. of secs. 21 & 28.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T23S	R9W
S 20	S 21
	S 28
	CC
	1977

from which

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 332300

PRIMARY CORNER DESCRIPTION SW Cor Sec. 21 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir, 35" dia., bears N.36½°E., 13½ lks., mkd: T23S R9W
S21 CC BT.
A Fir, 38" dia., bears S.50½°E., 59½ lks., mkd: T23S R9W
S28 CC BT.
From this point the SE cor. of sec. 20 only, bears S.0°26'E.,
4.80 chs.