

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 333400

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 20 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2638)</p> <p>-----</p> <p>Set Dogwood post 5 ft. long, 5" dia., 20" in ground for the sec. corner between Secs. 16, 17, 20, & 21, from which</p> <ul style="list-style-type: none">A Fir, 16" dia., bears N.10°E., 33 lks.A Fir, 20" dia., bears S.88°E., 26 lks.A Fir, 48" dia., bears S.60°W., 16 lks.A Fir, 20" dia., bears N.70°W., 9 lks.
<p>GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2691)</p> <p>-----</p> <p>I re-establish the cor. by setting a Hemlock post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 16, 17, 20, & 21, marked & witnessed as described by the surveyor general; I destroy all marks, referring to sec. 21 & 17.</p>
<p>Arthur R. Evans - Wit: J.I. Clinton and Elvin DeGrath - Feb. 25, 1952 - C.S. File 41/6-1</p> <p>-----</p> <p>Found - 4 OBTs</p> <ul style="list-style-type: none">16" Fir N.10°E., 33 lks. Stump20" Fir S.88°E., 26 lks.48" Fir, S.60°W., 16 lks.20" Fir, N.70°W., 9 lks. <p>NE & SE BTs do not apply, having been obliterated in re-survey of secs. 16 & 21, but are still in good shape.</p> <p>Set - 4"x4"x24" Hemlock stake for corner.</p> <ul style="list-style-type: none">24" Fir S.13°W., 35 ft., mkd: S20 T23S R9W CS BT (Nailed copper tags to stake & H. BT., labeled RE 2741)
<p>BLM Dependent resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14560)</p> <p>-----</p> <p>From the cor. of secs. 16 & 20 only, on the W. bdy of sec. 21 determined at record bearing and distance from the OBTs:</p> <ul style="list-style-type: none">A sawed Fir stump, 27" dia., bears N.10°E., 33 lks., no marks visible.A sawed Fir stump, 24" dia., bears S.88°E., 26 lks., no marks visible.A sawed Fir stump, 18" dia., bears N.70°W., 9 lks., with scribe marks BT visible on opened blaze <p>and a tree that I have no record</p> <p style="text-align: right;">continued next page</p>

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 333400

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 20 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock, 10" dia., bears N.87½°E., 102 lks., with scribe marks T23S R9W S21 BT visible on opened blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

	T23S R9W
	S 16 S 21
	S 20
	1969

from which the new BTs

A Hemlock, 9" dia., bears N.60½°W., 93 lks., mkd: T23S R9W S16 BT.

A Hemlock, 13" dia., bears S.60°W., 187 lks., mkd: T23S R9W S20 BT.

Fd. & used on BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16213-4)

Fd. Ok by Nick Juliano - 5/1979 - M 77-50