TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 333404

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 21 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2638)

Set Dogwood post 5 ft. long, 5" dia., 20" in ground for the sec. corner between Secs. 16, 17, 20, & 21, from which
A Fir, 16" dia., bears N.10°E., 33 lks.
A Fir, 20" dia., bears S.88°E., 26 lks.
A Fir, 48" dia., bears S.60°W., 16 lks.
A Fir, 20" dia., bears N.70°W., 9 lks.

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2691-2)

Page 2691
I re-establish the cor. by setting a Hemlock post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 16, 17, 20, & 21, marked & witnessed as described by the surveyor general; I destroy all marks, referring to sec. 21 & 17.
Page 2692
Set Hemlock post, 3 ft. long, 4" sq., 24" in the ground for NW cor. of sec. 21, mkd: T23S S16 on NE; R9W S21 on SE, S16 on SW and S16 on NW faces, with 4 notches on E & 3 notches on S edges, from which
A Hemlock, 20" dia., bears S.61°E., 35 lks., mkd: T23S R9W S21 BT.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16214)

Point for the NW cor. of sec. 21 only, at record distance in latitude from the cor. of secs. 16 & 20 only, and at record distance in departure from the ¼ sec. cor. of secs. 16 & 21; there is no remaining evidence of the orig. corner. This point falls in graveled road, 25 lks. wide, bears N.85°E., and W.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

S 16
|T23S
|R9W
|S 21
1977

from which
A Fir, 18" dia., bears S.15½°E., 69½ lks., mkd: T23S R9W S21 BT.
No other suitable trees available within limits.