

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2692)

Set a Hemlock post, 3 ft. long, 3" sq. 24" in the ground for 1/4 sec. cor. mkd: 1/4 S16 on N face and S21 on S face, from which:

- A Fir, 55" dia., bears N.72°E., 25 lks., mkd: 1/4 S16 BT.
- A Fir, 12" dia., bears S.4 1/2°E., 37 lks., mkd: 1/4 S21 BT.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16214-5)

The 1/4 sec. cor. of secs. 16 & 21, determined at the rec. bearing & dist. from the remains of an OBT:

- A sawed Fir stump, 70" dia., bears N.72°E., 25 lks., with scribe marks 1/4 S16 BT visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T23S R9W
1/4 S 16
S 21
1977

from which new BTs

- A Fir, 15" dia., bears N.27 1/4°E., 97 lks., mkd: 1/4 S16 BT.
- A Fir, 13" dia., bears S.45°W., 14 lks., mkd: 1/4 S21 BT.

Corner lies on south edge of graveled road, 25 lks. wide, bears N.65°E., and W.