TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2679)

Set a Yew post, 3 ft. long, 3" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ S28 on W face and 27 on E face, from which:
A Fir, 18" dia., bears S.55°E., 13 lks., mkd: ¼ S27 BT.
A Fir, 24" dia., bears S.28°W., 44 lks., mkd: ¼ S28 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & crew - June 1970 - C.S. File 54/60-49

Reported as not found.
Find N-S blazed line & tree blazed on all sides.

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16210)

Point for ¼ sec. cor. of secs. & , at proportionate distance; there is no remaining evidence of the orig. corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: T23S R9W

¼

S 28 | S 27

1977

from which
A Hemlock, 17" dia., bears N.47½°E., 35½ lks., mkd: ¼ S27 BT.
A Hemlock, 3" dia., bears N.68 3/4°W., 9 lks., mkd: X BT.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23306)

The ¼ sec. cor. of secs. 27 and 28, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.
from which the bearing trees mkd. by Bowder in 1977
A hemlock, 29" dia., bears N.47½°E., 23.4 ft., with a healed blaze.
A hemlock, 9" dia., bears N.68¾°W., 5.1 ft., with a healed blaze. (Record and slope distance, 5.9 ft.)
Drive an aluminum angle iron alongside the cor.